# MATER COMPANY EWS

#### PRODUCT CATALOG Volume III



Matthews Fan Company has been at the forefront of bringing unique ceiling, wall and portable fan products to both the residential and commercial markets since 1992.

Our innovative fans combine traditional, contemporary and industrial designs, retrospective elements and always high performance.

Matthews proudly integrates American parts and labor into the production of all of our products.

Visit one of our retailer partners or contact us for more information regarding our quality products and customization.

> Tel: 847-680-9043 Fax: 847-680-8140 www.MatthewsFanCo.com



and the



# MATTERS

#### Matthews' fans achieve some of the highest efficiency ratings in the industry through:

- airflow and ultra-quiet operation.
- Rotational fans reduce HVAC costs by mixing ambient air more thoroughly.

#### Matthews does not field destroy

• 95% of damaged and defective materials are recycled or re-purposed.

#### Matthews achieves low defect rates because:

- All fans are visually inspected before shipping.
- All rotational and oscillating fans are bench tested before shipping.

• DC Motor technology allows for large, powerful blades which provide more robust

• Directional and Wall fans provide columnar airflow which can be customized.

### MATTHEWS FAN COMPANY PRODUCTS



#### **MATTHEWS-GERBAR**



Ar Ruthiane pg. 64-65



Bianca Direcional pg. 66-67



Brisa 2000 pg. 68-69



Bruna Parede pg. 70-71



Duplo-Dinamico pg. 72-73



Italo Ventania pg. 74-75



Jarold Direcional pg. 76-77



Michelle Parede pg. 78-79





### Acqua



The Acqua 360° rotational fan is thoughtfully designed to resemble the molecular structure of water, Earth's most precious resource. The Acqua offers fluid lines and quiet axial rotation. Its fan heads can be infinitely positioned in 180-degree arcs for optimum air movement; the greater the angles of the motors to the horizontal support rods (up or down), the faster the axial rotation. A slow, controlled axial rotation is achieved by both fan head position and fan blade speed. Matthews rotational fans circulate heat and air-conditioning more efficiently than traditional paddle fans. Constructed of cast aluminum and heavy stamped steel, the Acqua carries a limited lifetime warranty.





ATLAS

A	ACQ	UA		
FINISH /	AND BLA	ΟΕ ΟΡΤ	IONS	
SKU#	AQ-XX-XX			
Standard	(Model+F Matte Blac		ade)	вк
Finishes	Textured E			ТВ
Blade Styles and Material	Solid Woo Solid Woo Solid Woo Metal w/ [ Metal w/ S	d / Mah d / Matt Decorati	ogany :e Black ve Cage	WDBW WD WDBK MTL MSAF
TE	CHNICAL		-	
Fan Weight	27 lbs			
Voltage	110 or 220	)		
Motor Type	AC			
Rotation	Yes			
Downrods Lengths	inches: 5,			
Field cuttable.	centimete	ers: 13, 2	5, 51, 76,	, 122, 183
Downrod Diameter	1 inch	1 46		
Overall Drop	16 inches			-
Environment	Damp loc Neither co chlorine c	bastal, s	altwater	
Ambience	Soothing	White N	oise	
Safety Certification	UL / CUL			
Warranty	Limited Li			
NEW JAN 21, 2020	DOE MO	FOR EF	FICIENC	Y DATA
Fan Head Options	Solid V	/ood	Metal \	with Guard
Fan Diameter	39 inches ,	/ 99 cm	37 inch	es / 94 cm
Fan Blade Diameter	16 inches ,	′ 41 cm	13 inch	es / 33 cm
Guard Options	No Cage Option		Safety Cage or Decorative Cage	
RPM (Low / High)	721 / 1199		1040 /	
CFM (Low / High)	2750 / 40	58	1825 /	3167
Watts (High)	101.25		80.50	
CFM/Watt (High)	40.80		39.34	
Blade Pitch	19°		31°	
LIGHT	KIT PHOT	OMETR	ICS	
Lamping (Replac	eable)		GU10 L	.ED
Remote Dimm	able		No	
Delivered Tempera	ture in K		2969	)
Delivered Lum	ens		337.3	0
CRI			94	
Watts			5	
Hours			36,00	0
Light kit longevit	y if used 6 H	lours/D	ay: 16.5	Years
STAI	NDARD EQ	UIPMEN	іт	
One dow	nrod of 10	inches /	25 cm	
Vaulted c	eiling canop	by for up	to 29°	
Black 3-speed RF re	mote	A	CESSOF	RY
control with rever		Decora on-dimr	-style, 3- nable wa	speed, III control
M OFF				



Minimal form with maximum efficiency. With a wide range of blade sizes, the Alessandra can accommodate any space. This thoughtfully crafted and versatile fan will complement any aesthetic and improves the health and comfort of any room. Highly customizable, the Alessandra is available in five different body finishes, seven blade options, and even an option with a CCT light kit as the Alessandra-LK. Suitable for wet locations. Backed by a limited lifetime warranty, our fans are of the highest quality and will dutifully perform for years to come. Constructed of cast aluminum and heavy stamped steel, the Alessandra has a limited lifetime warranty.





Con a serie a strange the

11/1/

	ALI	Ξ	SSA	١N		RA
		_	AND BLA	_	_	
	SKI		AK-XX	xx-xx	x-xx	∙Diameter)
	Standard Finish	nes	Brushed Brushed Matte B Matte V Texture	d Nicke lack Vhite	2	BRBR BN BK MWH TB
	Blade Finisł	nes	Barn W Brusheo Matte B Matte V Gray As Walnut	d Nicke lack Vhite	9	BW BN BK MWH GA WN
k with t blades	Fan Diame	ter	42 inch 56 inch 72 inch	es / 14	2 cm	42 56 72
1000		ΤE	CHNICA		CS	
	Fan Diamet	er	inches: centime			or 183
	 Blade Mater	ial	ABS		57, 142	51 105
	Overall Dro	-	1.20	/20 cr	n+dow	nrod length
	Fan Weig	•	17 lbs			
	Downrods Lengt		inches:	5. 10. 2	0.30.4	18.72
	Field cuttab Non-thread					, 76, 122, 183
	Downrod Diamet		1 inch			
	Voltag	ge	110 or 22	20		
	Motor Ty	се	DC			
ronze 'alnut blades	Environment		Wet location. All weather blade system. Neither outdoor coastal, saltwater nor chlorine compatible			
	Ambience		Silent		ompath	
	Safety Certification ETL / CETL					
	Warran	ty	Limited	Lifetim	ne	
	NEW JAN 21, 2	020	DOE MO	OTOR	EFFICIE	ENCY DATA
	Fan Diameter		2 inch /	56 i	nch /	72 inch /
			07 cm		2 cm	183 cm
	RPM (Low / High)			51 / 2		48 / 86*
	CFM (Low / High) Watts (High)		.37*		/ 7258	3727* / 9025
		20		32.61 220*		36.08* 339*
	CFM/Watt (High) Blade Pitch*	213 13°		13°		339* 13°
	*CFM data is app			13		15
			IDARD E	OLIIDA	1FNT	
			nrod of 10			m
			iling cand		,	
e with /ood blades	Black 6-speed RF remote control with reverse				vireless -style, d,	
	NOTE: Only o	om	patible w	ith incl	uded co	ntrollers.
	* Unipak is	not	available	for 72	" blade	option
r 183	Bar Woo Brush	n od ed	Options Gra Ast Matt	y 1 te	Walnu	e
	Nick	el	Blac		White	9

shown in Brushed Brass with 72" Matte White blades shown in Matte White with 72" Matte White blades

shown in Brushed Nickel with 56″ Barn Wood blades shown in Matte W with 42" Ash blac

### ATLAS Alessandra-LK

Minimal form with maximum efficiency. With a wide range of blade sizes, the Alessandra-LK can accommodate any space. This thoughtfully crafted and versatile fan will complement any aesthetic and improves the health and comfort of any room. Highly customizable, the Alessandra-LK is available in five different body finishes, seven blade options, and a dimmable 2700K-6500K CCT light kit. Suitable for damp locations. Backed by a limited lifetime warranty, our fans are of the highest quality and will dutifully perform for years to come. Constructed of cast aluminum and heavy stamped steel, the Alessandra-LK has a limited lifetime warranty.







	ALES	50	SAN	J۲		7-1	K
		_					- • •
	SKI	_	AKLK-	xxx	X-XXX-XX	(	tor)
	Standard Finish	nes	Brushee Brushee Matte E Matte V Texture	d Bra d Nie Black Vhite	ass ckel	BRBR BN BK MWH TB	
in Vhite " Gray des	Blade Finish	nes	Barn W Brushe Matte E Matte V Gray As Walnut	d Nie Black Vhite		BW BN BK MWH GA WN	
	Fan Diame	ter	56 inch	es /	107 cm 132 cm	42 56	5
		TE	72 inch CHNICA			72	
	Fan Diamet		inches:	42,	56 or 72 :: 107, 142	or 183	
	Blade Mater	ial	ABS				
	Overall Dro			5/20	cm+dow	nrod le	ngth*
	Fan Weig Downrods Lengt		17 lb*				
	Field cuttab Non-threade	le.		inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183			
Bronze	Downrod Diamet		1 inch				
Walnut blade	s Voltag Motor Typ	-	110 or 220 DC				
	Environme	Damp location for all finishes. Neither outdoor coastal, saltwater nor chlorine air compatible.					
	Ambien	Ce	Silent	JIII			
	Safety Certification         ETL / CETL           Warranty         Limited Lifetime						
					time		
	NEW JAN 21, 2	020	DOE M	ото	R EFFICI	ENCY [	DATA
	Fan Diameter		2 inch / 07 cm		5 inch / 42 cm		nch / cm
	RPM (Low/High)	-			/ 202*	48/8	
	CFM (Low/High)			169	2*/7258	3727*/	9025
	Watts (High)	-		32.		36.08	*
	CFM/Watt (High)	21		220		339*	
		17					
	Blade Pitch*	_		13°		13°	
l Brass ' Brushed	Blade Pitch* *CFM data is appr	roxi	mate			13°	
l Brass ' Brushed	Blade Pitch* *CFM data is appr LIG	roxii 6HT	mate KIT PHC		METRICS		ED
l Brass ' Brushed	Blade Pitch* *CFM data is appr	roxii GHT plac	mate KIT PHC ceable)		METRICS	13° rated L Yes	ED
l Brass ' Brushed	Blade Pitch* *CFM data is appr LIG Lamping (Re	roxii GHT plac mm	mate KIT PHC ceable) able		METRICS Integ	rated L	ED
l Brass ' Brushed	Blade Pitch* *CFM data is appr LlG Lamping (Re Remote Di Delivered Temp CR	roxii GHT plac mm pera	mate KIT PHC ceable) able		METRICS Integ	rated L Yes ariable 90	ED
l Brass ' Brushed	Blade Pitch* *CFM data is appr LlG Lamping (Re Remote Di Delivered Temp CR Wat	roxii FHT plac mm pera I ts	mate KIT PHC ceable) able		METRICS Integ	rated L Yes ariable 90 20	ED
l Brass ' Brushed	Blade Pitch* *CFM data is appr LlG Lamping (Re Remote Di Delivered Temp CR	roxii FHT plac mm pera l ts rs	mate KIT PHC :eable) able ture in K		METRICS Integ V	rated L Yes ariable 90	ED
Brass 7 Brushed lades	Blade Pitch* *CFM data is appr LIG Lamping (Re Remote Di Delivered Temp CR Wat Hou	roxii FHT plac mm pera l ts rs	mate KIT PHC eable) able ture in K	Lum	METRICS Integ V	rated L Yes ariable 90 20 0,000	ED
I Brass ' Brushed lades <b>atte</b>	Blade Pitch* *CFM data is appr LIG Lamping (Re Remote Di Delivered Temp CR Wat Hou 2700K 300	roxii plac mm pera l ts rs D	mate KIT PHC eable) able ture in K	DTO Lum OK	METRICS Integ V é	rated L Yes ariable 90 20 0,000	
Brass Brushed lades	Blade Pitch* *CFM data is appr LIG Lamping (Re Remote Di Delivered Temp CR Wat Hou 2700K 300 1431 15 Light kit long	roxii GHT plac mm pera I ts rs D D O K 21 evit	mate KIT PHC ceable) able ture in K eelivered 400 170 y if used	Lum OK 3 6 Hc	METRICS Integ V Eens 5000k 1688 surs/Day:	rated L Yes ariable 90 20 0,000	500K 1523
Brass Brushed lades	Blade Pitch* *CFM data is appr LIG Lamping (Re Remote Di Delivered Temp CR Wat Hou 2700K 300 1431 15 Light kit longe Si	roxii GHT plac mm Dera I ts rs D COK 21 Evity TAN	mate KIT PHC eable) able ture in K eelivered 400 170 y if used IDARD E	Lum 0K 3 6 Hc QUI	METRICS Integ V 6 ens 5000k 1688 purs/Day: PMENT	rated L Yes ariable 90 20 0,000 0,000 20 27.4 Ye	500K 1523
I Brass ' Brushed lades <b>atte</b>	Blade Pitch* *CFM data is appr LIG Lamping (Re Remote Di Delivered Temp CR Wat Hou 2700K 300 1431 15 Light kit long Si One d	roxii FHT plac mm Dera I ts rs DOK 21 Evity TAN Iowr	mate KIT PHC eable) able ture in K eelivered 400 170 y if used iDARD E	Lum OK 3 6 Hc QUI	METRICS Integ V V 6 ens 5000k 1688 ours/Day: PMENT hes / 25 c	rated L Yes ariable 90 20 0,000 0,000 27.4 Ye m	500K 1523
I Brass ' Brushed lades <b>atte</b>	Blade Pitch* *CFM data is appr LIG Lamping (Re Remote Di Delivered Temp CR Wat Hou 2700K 300 1431 15 Light kit long Si One d	roxii FHT plac mm Dera I ts rs DOK 21 Evity TAN Iowr	mate KIT PHC eable) able ture in K eelivered 400 170 y if used iDARD E	Lum OK 3 6 Hc QUI	METRICS Integ V 6 ens 5000k 1688 purs/Day: PMENT	rated L Yes ariable 90 20 0,000 20 0,000 20 27.4 Ye 27.4 Ye m 30°	500K 1523 ars
n Brass Brushed lades	Blade Pitch* *CFM data is appr LIG Lamping (Re Remote Di Delivered Temp CR Wat Hou 2700K 300 1431 15 Light kit long Si One d	roxii FHT plac mm Dera I ts rs DOK 21 Evity TAN Iowr	mate KIT PHC eable able ture in K eelivered 400 170 y if used DARD E prod of 10 illing cance	Lum OK 3 6 Hc QUI 0 inc opy Whit Decc 5-sp	METRICS Integ V V ens 5000k 1688 vurs/Day: PMENT hes / 25 c for up to 3 e wireless ora-style,	rated L Yes ariable 90 20 0,000 27.4 Ye m 50°	500K 1523
I Brass ' Brushed lades	Blade Pitch* *CFM data is appr LIG Lamping (Re Remote Di Delivered Temp CR Wat Hou 2700K 300 1431 15 Light kit longe S One d Vaulted Black 6-speed RF remote control	roxin plac mm pera l ts rs DOK 21 evity TAN lowr d ce	mate KIT PHC able ture in K elivered 400 170 y if used IDARD E mod of 10 illing cance V K	Lum OK 3 6 Hcc QUI Dinc Decc S-spy wall	METRICS Integ V V ens 5000k 1688 ours/Day: PMENT hes / 25 c for up to 3 for up to 3 for up to 3 for up to 3	rated L Yes ariable 90 20 0,000 27.4 Ye m 30°	500K 1523 ars
I Brass ' Brushed lades	Blade Pitch* *CFM data is appr LIG Lamping (Re Remote Di Delivered Temp CR Wat Hou 2700K 300 1431 15 Light kit longe S One d Vaulted Black 6-speed RF remote control with reverse	roxin plac mm pera I ts rs DOK 21 evity TAN lowr d ce	mate KIT PHC eable able ture in K eelivered 400 170 y if used DARD E brod of 10 illing cance illing cance patible w	Lum OK 3 6 Hcc QUI D inc Decc 5-spo wall ith in	METRICS Integ V V 6 ens 5000k 1688 ours/Day: PMENT hes / 25 c for up to 3 e wireless ra-style, eed, control	rated L Yes ariable 90 20 0,000 22 27.4 Ye m 30°	500K 1523 ars











#### LIGHT KIT PHOTOMETRICS

Lamping (Replaceable)	LED			
Delivered Temperature in K	3000			
Delivered Lumens	805 (x2)			
Watts	18 (x2)			
Hours	25,000			
Light kit longevity if used 6 Hours/Day: 11.4 Years				

### America

The America fan is a practical solution for both residential or commercial spaces with a more traditional aesthetic. It is available with either 42 or 52 inch diameters, along with an optional light kit. The blades are reversible as either white or light oak tone finish. The America carries a limited lifetime warranty.



#### USA

#### Applicability to Buy American Act:

TUF

Domestic Construction Materials Clause (Feb 2009): 52-225-9 (4)(2)(i). The cost of its components mined, produced, or manufactured in the United States exceeds 50 percent of the cost of all its components.

1

#### Breakdown of Origin of Materials:

Ceiling fan parts are made in Taiwan, a World Trade Organization Government Procurement Agreement country. Final assembly and UL 507 electrical compliance testing will be done in the US. US labor will be used in the assembly, handling and testing of this fan

ITEM	ORIGIN	% of COST of ITEM
Fan Components	Taiwan	41.18%
U.S. Labor MFC Facility'	* USA	34.46%
Domestic Shipping	USA	10.34%
International Shipping	USA	11.20%
US Duty	USA	1.96%
Shipping Insurance	USA	0.88%

US labor cost includes, but is not limited to: hands-on assembly, packaging and warehousing.

#### 1 Taiwan

#### Applicability to Buy American Act -

**Construction Materials Under Trade Agreements:** Construction Materials Clause (Aug 2009): 52-225-11 as prescribed in 25-1102. Ceiling fan parts and assembly comprise a "WTO GPA country

end-product."

#### Breakdown of Origin of Materials:

Ceiling fan is made in Taiwan, a World Trade Organization Government Procurement Agreement country.

ITEM Ceiling Fan Components/ Assembly Labor	<b>ORIGIN</b> Taiwan	<b>% of COST of ITEM</b> 74.59%
Shipping/ Handling / Insurance / Duty	USA	25.41%



	1ERICA	
		_
FINISH A	AND BLADE OPTIONS	
SKU#	AM-XX-XX-XX (Model+Diameter+Light)	
Light Kit	Without Light Kit Light Kit	NA LK
Fan Diameter	42 inches / 107 cm 52 inches / 132 cm	42 52
TE	CHNICAL SPECS	
Fan Diameters	inches: 42 or 52 centimeters: 107 or 132	
Blade Material	MDF	
Overall Drops with both standard downrods: 3" and 9"	13" without light kit and 3" 19" with light kit and 3" do 19" without light kit and 9" 25" with light kit and 9" do	wnrod ' downrod
Fan Weight	21 lbs	
Downrods Lengths Field cuttable. Non-threaded	inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 1	122, 183
Downrod Diameter	1 inch	
Lead length	78"	
Voltage	110 or 220	
Motor Type	AC	
Motor size	172 mm x 14 mm (3 speeds and forward/rev	erse)
Mounting	Vaulted ceiling canopy for	up to 29°
Control	Pull-chain (Wall control available as a	ccessory)
Light kit	Available as accessory wi X2 GU24 sockets and fros bowl. LED lamps.	
Ambience	Silent	
Safety Certification	UL Listed - Dry Location	
Warranty	Limited Lifetime	
STAN	IDARD EQUIPMENT	
One dow	nrod of 3 inches / 8 cm	
	nrod of 9 inches / 23 cm	
Vaulted ce	iling canopy for up to 30°	

NEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA					
	With 3" Downrod	With 3" Downrod	With 9" Downrod	With 9" Downrod	
	42 inch 107 cm	52 inch 132 cm	42 inch 107 cm	52 inch 132 cm	
RPM (Low/High)	87 / 243	54 / 162	93 / 249	57 / 166	
CFM (Low/High)	1488/4204	1313/4083	1419/4050	1699/4643	
Watts (High)	60	64.67	61	59	
CFM/Watt (High)	58	63.14	58	79	
Blade Pitch	12°	12°	12°	12°	

shown in Textured Bronze with Metal Blades and Decorative Cage



# Dagny



The double-headed 360° rotational fan, Dagny, with cylindrical central housing and straight, parallel arms, is designed in the retrospective aesthetic. The Dagny offers smooth and quiet axial rotation. Its fan heads can be infinitely positioned in 180-degree arcs for optimum air movement; the greater the angles of the motors to the horizontal support rods (up or down), the faster the axial rotation. A slow, controlled axial rotation is achieved by both fan head position and fan blade speed. Matthews rotational fans circulate heat and air-conditioning more efficiently than traditional paddle fans. Constructed of cast aluminum and heavy stamped steel, the Dagny carries a limited lifetime warranty. The Dagny is also available with a light kit as the *Dagny-LK*.





C	) AGN	Y
FINISH	AND BLADE O	PTIONS
SKU#	DG-XX-XXXX (Model+Finish+E	
Standard Finish	Textured Bronze Matte Black	ТВ ВК
Blade Styles and Material	Solid Wood / Ba Solid Wood / Ma Solid Wood / Ma Metal w/ Decora Metal w/ Safety	hogany WD tte Black WDBK tive Cage MTL
TE	ECHNICAL SPEC	:S
Fan Weight	22 lbs	
Voltage	110 (Contact us f	or 220 conversion)
Motor Type	AC	
Rotation	Yes	
Downrods Lengths Field cuttable, Non-Threaded	inches: 5, 10, 20 centimeters: 13,	, 30, 48, 72 25, 51, 76, 122, 183
Downrod Diameter	1 inch	
Overall Drop	14 inches / 36 cn	n + downrod length
Environment	Damp locations Neither coastal, chlorine compat	saltwater nor
Ambience	Soothing White	Noise
Safety Certification	UL / CUL	
Warranty	Limited Lifetime	
NEW JAN 21, 202	0 DOE MOTOR E	FFICIENCY DATA
Fan Head Options	Solid Wood	Metal with Guard
Fan Diameter	41 inches / 104 c	m 39 inches / 99 cm
Fan Blade Diameter	16 inches / 41 cm	13 inches / 33 cm
Guard Options	No Cage Option	Safety Cage or Decorative Cage
RPM (Low / High)	1012 / 1445	1035 / 1448
CFM (Low / High)	2565 / 4168	2199 / 3169
Watts (High)	87.26	80.69
CFM/Watt (High)	50	42
Blade Pitch	19°	31°
STA	NDARD EQUIPME	NT
	vnrod of 10 inches	
Vaulted o	eiling canopy for	·
Black 3-speed RF re control with rever	mote Deco	ACCESSORY pra-style, 3-speed, mmable wall control

shown in Brushed Nickel with Mahogany blades

## Dagny LK

With clean, fluid lines, the Dagny LK 360° rotational fan is a striking centerpiece in any space. Its movement about its cylindrical center housing is smooth and quiet. Dagny LK's dual fan heads can be infinitely positioned in 180-degree arcs for optimum and customized air movement. As the angle between the fan heads and the horizontal support rods is increased, so does the speed of Dagny LK's axial rotation. Matthews rotational fans circulate heat and air conditioning more efficiently than traditional paddle fans. Constructed from cast aluminum and heavy stamped steel, the Dagny LK carries a limited lifetime warranty. This model is also available without a light kit as the *Dagny*.



41" / 104 cm wood fan head | 39" / 99 cm metal fan head

2" / 5 cm

Downrods available in inches: 5, 10, 20, 30, 48 or 72

Increasing Angles of Fan Heads to Support Poles Increases Speed of Axial Rotation Optimum Fan Head Position is 60°

6" / 15 cm diameter

16" / 41 cm Wood Blades

ATLAS

FINISH AND BLADE OPTIONS         SKU#       DGLK-XX-XXXX (Model+Finish+Blade)         Standard Finishes       Brushed Nickel       BN Matte Black         Blade Styles and Material       Solid Wood / Barn Wood Solid Wood / Mahogany Solid Wood / Matte Black Metal w/ Decorative Cage       WDBW WD         Blade Styles and Material       Solid Wood / Matte Black Metal w/ Decorative Cage       WTL MSAF         TECHNICAL SPECS         Overall Drop       14 inches / 41 cm + downrod length         Fan Weight       22 lbs         Voltage       110 (Contact us for 220 conversion         Motor Type       AC         Rotation       Yes         Downrods Lengths <i>Field cuttable</i> , <i>Non-Threaded</i> inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183         Downrod Diameter       1 inch         Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible         Ambience       Soothing White Noise         Safety Certification       UL / CUL         Warranty       Limited Lifetime         NEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA         Fan Head Options       Solid Wood       Metal with Gua	 V		
SKU#       (Model+Finish+Blade)         Standard Finishes       Brushed Nickel Matte Black Textured Bronze       BN BK Textured Bronze         Blade Styles and Material       Solid Wood / Barn Wood Solid Wood / Mahogany Solid Wood / Matte Black Metal w/ Decorative Cage       WDBW WD WDBK MtL MSAF         TECHNICAL SPECS         Overall Drop       14 inches / 41 cm + downrod length         Fan Weight       22 lbs         Voltage       110 (Contact us for 220 conversion         Motor Type       AC         Rotation       Yes         Downrods Lengths <i>Field cuttable, Non-Threaded</i> inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183         Downrod Diameter       1 inch         Environment       Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible         Ambience       Soothing White Noise         Safety Certification       UL / CUL         Warranty       Limited Lifetime         NEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA         Fan Head Options       Solid Wood	 V		
Standard FinishesMatte Black Textured BronzeBK TBBlade Styles and MaterialSolid Wood / Barn Wood Solid Wood / Mahogany Solid Wood / Mahogany Solid Wood / Matte Black Metal w/ Decorative CageWDBW WD WDBK MTL MSAFTECHNICAL SPECSOverall Drop14 inches / 41 cm + downrod lengtlFan Weight22 lbsVoltage110 (Contact us for 220 conversion Motor TypeMotor TypeACRotationYesDownrods Lengths <i>Field cuttable</i> , Non-Threadedinches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183Downrod Diameter1 inchEnvironmentDamp locations for all finishes Neither coastal, saltwater nor chlorine compatibleAmbienceSoothing White NoiseSafety CertificationUL / CULWarrantyLimited LifetimeNEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA Fan Head OptionsSolid Wood	v		
Blade Styles and MaterialSolid Wood / Mahogany Solid Wood / Matte Black Metal w/ Decorative CageWD WDBK MTL MSAFTECHNICAL SPECSOverall Drop14 inches / 41 cm + downrod lengthFan Weight22 lbsVoltage110 (Contact us for 220 conversion Motor TypeMotor TypeACRotationYesDownrods Lengths <i>Field cuttable</i> , Non-Threadedinches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183Downrod Diameter1 inchEnvironmentDamp locations for all finishes Neither coastal, saltwater nor chlorine compatibleAmbienceSoothing White NoiseSafety CertificationUL / CULWarrantyLimited LifetimeNEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA Fan Head OptionsSolid WoodMetal with Guard	v		
Overall Drop14 inches / 41 cm + downrod lengthFan Weight22 lbsVoltage110 (Contact us for 220 conversionMotor TypeACRotationYesDownrods Lengths Field cuttable, Non-Threadedinches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183Downrod Diameter1 inchEnvironmentDamp locations for all finishes Neither coastal, saltwater nor chlorine compatibleAmbienceSoothing White NoiseSafety CertificationUL / CULWarrantyLimited LifetimeNEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA Fan Head OptionsSolid Wood			
Fan Weight22 lbsVoltage110 (Contact us for 220 conversionMotor TypeACRotationYesDownrods Lengths Field cuttable, Non-Threadedinches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183Downrod Diameter1 inchDownrod Diameter1 inchEnvironmentDamp locations for all finishes Neither coastal, saltwater nor chlorine compatibleAmbienceSoothing White NoiseSafety CertificationUL / CULWarrantyLimited LifetimeNEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA Fan Head OptionsSolid WoodMetal with Guard			
Voltage110 (Contact us for 220 conversionMotor TypeACRotationYesDownrods Lengths Field cuttable, Non-Threadedinches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183Downrod Diameter1 inchDownrod Diameter1 inchEnvironmentDamp locations for all finishes Neither coastal, saltwater nor chlorine compatibleAmbienceSoothing White NoiseSafety CertificationUL / CULWarrantyLimited LifetimeNEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA Fan Head OptionsSolid WoodMetal with Guar	th		
Motor TypeACRotationYesDownrods Lengths Field cuttable, Non-Threadedinches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183Downrod Diameter1 inchDownrod Diameter1 inchEnvironmentDamp locations for all finishes Neither coastal, saltwater nor chlorine compatibleAmbienceSoothing White NoiseSafety CertificationUL / CULWarrantyLimited LifetimeNEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA Fan Head OptionsSolid Wood			
RotationYesDownrods Lengths Field cuttable, Non-Threadedinches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183Downrod Diameter1 inchEnvironmentDamp locations for all finishes Neither coastal, saltwater nor chlorine compatibleAmbienceSoothing White NoiseSafety CertificationUL / CULWarrantyLimited LifetimeNEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATAFan Head OptionsSolid WoodMetal with Guaranty	ר)		
Downrods Lengths       inches: 5, 10, 20, 30, 48, 72         Field cuttable,       centimeters: 13, 25, 51, 76, 122, 183         Downrod Diameter       1 inch         Downrod Diameter       1 inch         Environment       Damp locations for all finishes         Neither coastal, saltwater nor chlorine compatible         Ambience       Soothing White Noise         Safety Certification       UL / CUL         Warranty       Limited Lifetime         NEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA         Fan Head Options       Solid Wood			
Field cuttable, Non-Threaded       Inchest 5, 10, 20, 30, 46, 72         centimeters: 13, 25, 51, 76, 122, 183         Downrod Diameter       1 inch         Environment       Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible         Ambience       Soothing White Noise         Safety Certification       UL / CUL         Warranty       Limited Lifetime         NEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA         Fan Head Options       Solid Wood			
Environment       Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible         Ambience       Soothing White Noise         Safety Certification       UL / CUL         Warranty       Limited Lifetime         NEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA         Fan Head Options       Solid Wood	3		
Environment       Neither coastal, saltwater nor chlorine compatible         Ambience       Soothing White Noise         Safety Certification       UL / CUL         Warranty       Limited Lifetime         NEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA         Fan Head Options       Solid Wood			
Safety Certification       UL / CUL         Warranty       Limited Lifetime         NEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA         Fan Head Options       Solid Wood         Metal with Gue			
Warranty     Limited Lifetime       NEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA       Fan Head Options     Solid Wood			
NEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA           Fan Head Options         Solid Wood         Metal with Guilding			
Fan Head Options Solid Wood Metal with Gu			
	4		
Ean Diamator 41 inches / 104 am 70 inches / 00	lard		
Fan Diameter 41 inches / 104 cm 39 inches / 99	cm		
Fan Blade Diameter 16 inches / 41 cm 13 inches / 33 c	cm		
Guard Options         No Cage Option         Safety Cage or Decorative Cage			
RPM (Low / High)         757 / 1256         1069 / 1442           CEM (Low / High)         2557 / 4171         1044 / 7067			
CFM (Low / High)         2557 / 4171         1844 / 3067           Watts (High)         87.36         80.50			
Watts (High)         87.36         80.30           CFM/Watt (High)         50         39			
Blade Pitch 19° 31°			
LIGHT KIT PHOTOMETRICS			
Light Kit Photometrics Lamping (Replaceable) Integrated LED			
Remote Dimmable Yes			
Delivered Temperature in K 2969			
Delivered Lumens 523.7			
CRI 90			
Watts 18	18		
Hours 50,000			
Light kit longevity if used 6 Hours/Day: 22.8 Years			
STANDARD EQUIPMENT			
One downrod of 10 inches / 25 cm			
Vaulted ceiling canopy for up to 29°			
Black 3-speed RF remote ACCESSORY			
control with reverse Decora-style, 3-speed, non-dimmable wall control			
non-diminable wait control	01		

shown in Brushed Nickel with Barn Wood Blades

shown in Textured Bronze with Barn Wood Blades

shown in Matte Black with Matte Black Blades

shown in Textured Bronze with Metal Blades and

Decorative Cage

centimeters: 13, 25, 51, 76, 122, or 183

13" / 33 cm Aetal Blades



Both ceiling fan and LED pendant, Dana is our most versatile fixture. Her diminutive blades and LED light kit are concealed by intricate, organically inspired metal work finished in Matte Black, Matte White, Brushed Bronze, or Brushed Brass. Constructed of cast aluminum and heavy stamped steel, the Dana carries a limited lifetime warranty.









shown	in	Matte	White
5110 1011		Matte	vvinte



2,	or	183	

DANA						
DANA						
FINISH AND BLADE OPTIONS						
SKU#	DM-X (Mod	( <b>XXX</b> el+Finish)				
Standard Finishes	Brush Matte	ned Brass ned Bronze Black White	BRBR BB BK MWH			
TE(	CHNIC	AL SPECS				
Fan Diameter	20 inc	hes / 51 cm	1			
Blade Material	Rubbe	er				
Overall Drop	Prop 16 inches / 41 cm + downrod length					
Fan Weight	23 lbs					
Voltage	110 or	220				
Motor Type	AC					
Downrods Lengths Field cuttable, Non-Threaded		s: 5, 10, 20, neters: 13, 2	30, 48, 72 25, 51, 76, 122, 183			
Downrod Diameter	1 inch					
Environment Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible						
Ambience	Sooth	ing White N	loise			
Safety Certification	UL/C	CUL				
Warranty Limited Lifetime						
NEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA						
RPM (Low / High)	1095 ,	/ 1666				
CFM (Low / High)	691/	1100				
Watts (High)	32					
CFM/Watt (High) 42						
Blade Pitch	31°					
LIGHT KIT PHOTOMETRICS						
Lamping (Replac	eable)	I	ntegrated LED			
Remote Dimm	able		Yes			
Delivered Temperat	ture in l	<	2923			
Delivered Lumens 578						
CRI 93.8						
Watts 24						
Hours			49,000			
Light kit longevity	if usec	l 6 Hours/Da	ay: 22.4 Years			
STAN	DARD	EQUIPME	NT			
One dowr	nrod of	10 inches /	25 cm			
Vaulted ce	iling ca	anopy for up	o to 29°			
	Ligh	t cover				
Black 3-speed RF remote control with reverse		AC Decora-sty 3-speed, non-dimm wall contro	able			

shown in Brushed Nickel with Metal blades and Decorative Cage

### Diane



The Diane directional fan head provides maximum airflow with a sweeping 90° forward and reverse oscillation. The Diane can be hung in small, awkward spaces or in front of HVAC ducts to improve the efficiency of heating, ventilation or air conditioning of any space. Constructed of cast aluminum and heavy stamped steel, the Diane carries a limited lifetime warranty.



shown in Textured Bronze with Mahogany blades hown in ronze w Metal blac Decorative own in latte Black with Matte Black blades shown in Polished Chrome with Metal blades and Decorative Cage hown in Polished Chrome with Barn Wood blades 6" / 15 cm diamete 2" / 5 cm --------Downrods available in inches: 5, 10, 20, 30, 48 or 72 centimeters: 13, 25, 51, 76, 122, or 183 10" / 25 cm **((1)**) 90° forward & reverse sweeping oscillation

16" / 41 cm

ATLAS

Textured	
ith	
des and	
e Cade	







-		
•		

12" / 30 cm

13" / 33 cm

Black 3-speed RF remote control



DIANE

FINISH AND BLADE OPTIONS

DI-XX-XXXX

Matte Black

Brushed Nickel

Polished Chrome

**Textured Bronze** 

TECHNICAL SPECS

110 or 220

12 lbs

AC

Yes

1 inch

(Model+Finish+Blade)

Solid Wood/Barn Wood

Solid Wood/Mahogany

Metal w/ Safety Cage

Solid Wood/Matte Black

inches: 5, 10, 20, 30, 48, 72

centimeters: 13, 25, 51, 76, 122, 183

14 inches / 36 cm + downrod length

12 inches / 30 cm + downrod length

Damp locations for all finishes

Neither coastal, saltwater nor

chlorine compatible

Soothing White Noise

ETL / CETL

Limited Lifetime NEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA

Solid Wood

16 inches/41 cm

16 inches / 41 cm

No Cage Option

865 / 1325

1441 / 2152

STANDARD EQUIPMENT One downrod of 10 inches / 25 cm

51.37

44

19°

Metal w/ Decorative Cage MTL

ΒN

BK

CR

ΤВ

WD

WDBW

WDBK

MSAF

SKU#

Standard Finishes

Blade Styles

and Material

Fan Weight

Motor Type

Oscillation

Field cuttable.

Non-threaded Downrod Diameter

Downrods Lengths

Overall

Drop

Voltage

Metal

Blades

Wood

Blades

Environment

Safety Certification

Fan Head Options

Fan Blade Diameter

CFM (Low / High)

CFM/Watt (High)

Fan Diameter

Guard Options RPM (Low / High)

Watts (High)

Blade Pitch

Ambience

Warranty

Decora-style, 3-speed wall control in white



Metal with Guard

13 inches / 33 cm

13 inches / 33 cm

Decorative Cage or Safety Cage

900 / 1377

1068 / 1345

46.14

31

31°

23

shown in Gloss White with Barn Wood blades

### COASTAL WET LOCATION 200 100% 316 MARINE GRADE STAINLESS STEEL

### Donaire

With teardrop motor housing, the 52" Donaire 316 marine grade stainless steel coastal wet location ceiling fan is transitional in design. Donaire is finished in brushed bronze, brushed stainless, or gloss white, equipped with all weather blades and 16W LED dimmable light kit with optional metal cover. Constructed of entirely 316 marine grade stainless steel, the Donaire carries a limited lifetime warranty.





ATLAS





shown in Brushed Stainless

shown in Brushed Bronze with Brushed Bronze blades and optional metal cover

> with Barn Wood blades and optional metal cover

shown in Matte Black with Black blades and optional metal cover

6" / 15 cm diameter

10" / 25 cm

shown in Gloss White with Gloss White blade

shown in Brushed Stainless with Brushed Stainless blades

2" / 5 cm

6.5" / 17 cm

Downrods available in inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183

Blade Pitch 14°

6" / 15 cm

DONAIRE
---------

FINISH A	AND BLADE OPTIONS
SKU#	DA-XX-XX (Model+Finish+Blade)
Standard	Matte Black <b>BK</b> Brushed Bronze <b>BB</b>
Finishes	Brushed Stainless BS
	Gloss White WH Black BK
Blade Finish	Black BK Barn Wood Tone BW Brushed Bronze BB Brushed Stainless BS Gloss White WH
TE	CHNICAL SPECS
Fan Diameter	52 inches / 132 cm
Blade Material	ABS
Overall Drop	8.5 inches/22 cm + downrod length
Fan Weight	29 lbs
Voltage	110 or 220
Motor Type	AC
Downrods Lengths Field cuttable, Non-Threaded	inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183
Downrod Diameter	1 inch
	Coastal and wet locations
Environment	All weather blade system
Ambience	Silent
Safety Certification	UL / CUL
Warranty	Limited Lifetime
NEW JAN 21, 2020	DOE MOTOR EFFICIENCY DATA
RPM (Low / High)	55 / 172
CFM (Low / High)	1775 / 6013
Watts (High)	58.62
CFM/Watt (High)	111
Blade Pitch	14°
LIGHT	KIT PHOTOMETRICS
Lamping (Replac	ceable) Integrated LED
Remote Dimma	
Delivered Temperat	ture in K 3017
Delivered Lum	iens 725
CRI	90
Watts	16
Hours	60,000
	/ if used 6 Hours/Day: 27.4 Years DARD EQUIPMENT
	nrod of 10 inches / 25 cm
	eiling canopy for up to 29°
	Light cover
	ACCESSORY
Black 3-speed RF remote control with reverse	Decora-style, 3-speed, non-dimmable wall control
Blade Options Black Brushed Bronze	Brushed Barn Gloss Stainless Wood White



and greater motor optimization. Equally important is Eliza's stationary visual statement which combines modern utility with minimalist geometry. Constructed of cast aluminum and heavy stamped steel, the Eliza has a limited lifetime warranty.





	C	ELIZA					
	FINISH A	ND BLADE OPTIONS					
oss White blades	SKU#	<b>EK-XX-XX</b> (Model+Finish+Blade)					
	Standard Finishes	Brushed Nickel BN Gloss White WH Matte Black BK					
	Blade Finish	Barn WoodBWBrushed NickelBNGloss WhiteWHGray AshGAMatte BlackBKOld OakOOWalnutWN					
	TEC	CHNICAL SPECS					
	Fan Diameter	56 inches / 142 cm					
	Blade Material	ABS					
	Overall Drop	12 inches/30 cm+downrod length					
	Fan Weight	17 lbs					
	Voltage	110 or 220					
	Motor Type	DC					
oss White lood blades	Downrods Lengths Field cuttable, non-threaded	inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183					
	Downrod Diameter	1 inch					
	Environment	Wet locations for all finishes All weather blade system. Neither coastal, saltwater nor chlorine compatible					
	Ambience	Silent					
	Safety Certification	ETL / CETL					
	Warranty	Limited Lifetime					
	NEW JAN 21, 2020	DOE MOTOR EFFICIENCY DATA					
	RPM (Low / High)	55 / 172					
	CFM (Low / High)	1633 / 5439					
	Watts (High)	33.13					
	CFM/Watt (High) Blade Pitch	167 27°					
ushed Nickel		DARD EQUIPMENT					
d Nickel blades		· · · ·					
	One downrod of 10 inches / 25 cm Vaulted ceiling canopy for up to 30°						
	Black 6-speed RF remote control with reverse	White wireless Decora-style, 6-speed, wall control with reverse					
	NOTE: Only comp	atible with included controllers.					
	Blade Opt	ions					
or 183	Barn Wood	Gray Old Ash Oak Walnut					
cm width	Brushed Nickel	Matte Gloss Black White					



shown in Matte Black with Brushed Nickel blades

### Eliza-H Geometry in Motion

Bru

shown in Matte Black with Matte Black blades

shown in Brushed Nickel with Barn Wood blades

Designed by Chicago architect Stephen Katz in 2014, the Eliza-H ceiling-mount fan blends a beautiful technically derived form with superior function and movement. The unique blade shape is designed to maximize air movement at the outer edge of the blade. The result is more efficient air velocity rings, less blade drag and greater motor optimization. Equally important is Eliza-H's stationary visual statement which combines modern utility with minimalist geometry. Constructed of cast aluminum and heavy stamped steel, the Eliza-H has a limited lifetime warranty.





ATLAS



shown in Gloss White with Old Oak blades





shown in Brushed Nickel with Walnut blades





FINISH A	ND BLADE OPTIONS			
SKU#	<b>EKH-XX-XX</b> (Model+Finish+Blade)			
Standard Finishes	Brushed Nickel BN Gloss White WH Matte Black BK			
Blade Finish	Barn WoodBWBrushed NickelBNGloss WhiteWHGray AshGAMatte BlackBKOld OakOOWalnutWN			
TEC	CHNICAL SPECS			
Fan Diameter	56 inches / 142 cm			
Blade Material	ABS			
Overall Drop	10 inches / 25 cm			
Fan Weight	14 lbs			
Voltage	110 or 220			
Motor Type	DC			
Environment	Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible			
Ambience	Silent			
Safety Certification	ETL / CETL			
Warranty	Limited Lifetime			
NEW JAN 21, 2020	DOE MOTOR EFFICIENCY DATA			
RPM (Low / High)	52 / 175			
CFM (Low / High)	1123 / 4034			
Watts (High)	33.49			
CFM/Watt (High)	122			
Blade Pitch	27°			
STAN	DARD EQUIPMENT			
Black 6-speed RF remote control with reverse	White wireless Decora-style, 6-speed, wall control with			

reverse

NOTE: Only compatible with included controllers.

ELIZA-H

shown in Matte Black with Gray Ash blades



The Irene-3 is rustic, yet strikingly modern with three neatly joined, solid matte black, matte white, walnut, or barn wood tone blades. A spherical motor housing complements its minimal profile. Irene-3 is streamline while still appearing warm and natural. Constructed of cast aluminum and heavy stamped steel, the Irene-3 has a limited lifetime warranty.



and the second second



### **IRENE-3**

FINIS	H.		ADE OPTION	IS		
SKI		IR3-XX	-XXX-XX			
			+Finish+Blade			
Standa Finish		Matte E Texture	Black d Bronze	BK TB		
Blade Finish	nes	Barn W Gray As Light M Matte B Matte V Walnut	laple Black Vhite	BW GA LM BK MWH WA		
Fan Diame	ter	52 inch	es / 107 cm es / 132 cm ies / 152 cm	42 52 60		
	ΤE	CHNICA	L SPECS			
Fan Diamet	er		42, 52 or 60 ters: 107, 132	or 152		
Blade Mater	ial	CNC Cu	t Solid Wood			
Overall Dro	р	12 inche	es/30 cm+do	wnrod length		
Fan Weig	ht	17 lbs				
Downrods Lengt Field cuttab Non-threade	le.		5, 10, 20, 30, eters: 13, 25, 5	48, 72 1, 76, 122, 183		
Downrod Diameter 1 inch						
Voltage 110 or 220						
Motor Type DC						
Environme	nt	Neither	ocations for a coastal, saltw compatible			
Ambien	ce	Silent				
Safety Certification	on	ETL / C	ETL			
Warranty Limited Lifetime						
NEW JAN 21, 20	020	DOE MO	OTOR EFFICI	ENCY DATA		
Fan Diameter		2 inch / 07 cm	52 inch / 132 cm	60 inch / 152 cm		
RPM (Low/High)	52	/ 231	51 / 196	52 / 160		
CFM (Low/High)	54	1 / 3517	1531 / 6168	2088 / 6984		
Watts (High)	17.0		32.12	31.67		
CFM/Watt (High)	163		185	218		
Blade Pitch	15°		15°	15°		
			QUIPMENT			
			) inches / 25 c			
Vaulteo	d ce	iling cand	ppy for up to 3			
Black 6-speed RF remote control with reverse		0	White wireles: Decora-style, 6-speed, wall control with reverse			
NOTE: Only o	com	patible w	ith included co	ontrollers.		
Blade	- C	Option	s			





shown in Polished Chrome with 52" Barn Wood blades

> shown in Brushed Bronze with 42" Barn Wood blades

shown in Brushed Brass with 60" Matte White blades

shown in Barn Wood with 60" Light Maple blades

> shown in Walnut with 42" Walnut blades

Blade Pitch 15°

10" / 25 cm

7" / 18

2" / 5 cm

shown in Textured Bronze with

shown in Matte Black with 42" Matte Black blade

shown in Brushed Nickel with 42" Gray Ash blades

> shown in Light Maple with 42" Walnut blades

> > shown in

Brushed Pewter with 42" Walnut blades

42" Walnut blades

shown in Gloss White with 42" Barn Wood blades

1

ATLAS

### Irene-3H

The Irene-3H ceiling-mount fan is rustic, yet strikingly modern with three neatly joined, solid wood matte black, matte white, walnut, or barn wood tone blades. A cylindrical motor housing complements its minimal profile. Irene-3H is streamline while still appearing warm and natural. Constructed of cast aluminum and heavy stamped steel, the Irene-3H has a limited lifetime warranty.

<b>₽</b> DC <sup>4</sup>		— Product Features ·	Ā	
DC Motor	J Damp Location	Silent	Remote Control	Wall Control

		R	EN	E-3H	4		
	FINIS	5H /	AND BLA	DE OPTIO	NS		
	SKI	J#		XXX-XXX-X			
	Standard Finish	es	Barn We Brushec Brushec Brushec Gloss W Light M Matte B Polishec	ood Brass Bronze Nickel Pewter /hite aple	le+Diameter) BW BRBR BB BN BP WH LM BK CR TB WN		
	Blade Finisł	nes	Barn Wo Gray As Light Mo Matte B Matte W Walnut	aple lack /hite	BW GA LM BK MWH WA		
	Fan Diame	ter	52 inch	es / 107 cm es / 132 cm es / 152 cm	42 52 60		
1		ΤE	CHNICAI				
	Fan Diamet	er		42, 52 or 60			
and the second se	Blade Mater	ial		ters: 107, 13 t Solid Wood			
	Overall Dro			s/25 cm			
. 9	Fan Weig	ht	11 lbs				
Contraction of the second	Volta	ge	110 or 220				
	Motor Ty	DC					
	Environme	chlorine compatible.					
	Ambien		Silent				
	Safety Certificatio Warran		ETL / C				
-	Warranty Limited Lifetime NEW JAN 21, 2020 DOE MOTOR EFFICIENCY DATA						
	Fan Diameter	4	2 inch / 07 cm	52 inch / 132 cm	60 inch / 152 cm		
	RPM (Low/High)		/ 231	51 / 193	52 / 155		
	CFM (Low/High) Watts (High)	740 17.0	6 / 3743 61	1254 / 5320 32.38	6 1755 / 5720 32.08		
1	CFM/Watt (High)	176		160	181		
	Blade Pitch	15°		15°	15°		
	S'	TAN	IDARD E	QUIPMENT			
	Black 6-speed RF remote control with reverse			White wirele Decora-style 5-speed, wal control with everse	,		
	NOTE: Only o	com	patible wi	th included c	ontrollers.		
cm	7° / 18 cm width		Blade Barn Wood Matte Black	d Ash Matt	e Walaut		
-	LISTED						

42", 52" or 60" / 107 cm, 132 cm or 152 cm

own in Brushed Brass th 52" Walnut blades

shown in Gloss White with 60" Matte White blades

shown in Matte Black with 52" Matte Black blades

shown in Brushed Nickel with 52" Barn Wood plades

### Irene-3HLK

The Irene-3HLK ceiling-mount fan is rustic, yet strikingly modern with three neatly joined, solid wood matte black, matte white, walnut, or barn wood tone blades. A cylindrical motor housing complements its minimal profile. Irene-3HLK is streamline while still appearing warm and natural. Constructed of cast aluminum and heavy stamped steel, the Irene-3HLK has a limited lifetime warranty.



12.20

-

Brushed Pewter with 42" Matte White blades

10" / 25 cm

2" / 5 cm

-

shown in

shown in Walnut with 42"

Walnut blades

shown in

Polished Chrome with 42" Matte Black blades 7" / 18 cm 12" / 30 cm

Blade Pitch 15°



1

ATLAS

I							
	IR	Ε	NE	-3	SHL	K	
S	FINIS	ін <i>А</i>	AND BL	ADE	OPTION	S	
	SKU# IR3HLK-XXXX-XXX-XX (Model+Finish+Blade+Diameter)						
		- • •	(Model Barn W			+Diameter BW	)
	Standard Finish	es	Barrishe Brushe Brushe Light M Gloss V Matte E Polishe Texture Walnut	d Bra d Bra d Nia d Pe laple Vhite Black d Ch ed Br	ass onze ckel wter e c inome	BRBF BB BN BP LM WH BK CR TB WN	2
	Blade Finisł	nes	Barn W Matte E Matte \ Walnut	Black White Ton	e	BW BK MWH WA	1
	Fan Diame	ter	42 inches / 107 cm 52 inches / 132 cm 60 inches / 152 cm			42 52 60	
		TE	ECHNICA	L SP	ECS		
shown in	Fan Diamet	er			52 or 60 s: 107, 132	or 152	
Textured Bronze with 60" Walnut	Blade Material CNC Cut Solid Woo						
blades	Overall Dro		12 inches/30 cm				
	Fan Weig Voltag		12 lbs 110 or 2	20			
	Motor Ty	-	DC				
	Environme		Neither chlorin	соа	ions for a stal, saltv mpatible.	ll finishes. vater nor	
3	Ambien Safety Certificatio		Silent ETL / C	יבדי			
shown in Brushed Bronze	Warran		Limited		time		
with 52" Barn Wood blades	NEW JAN 21, 20	3				ENCY DAI	A
Wood bildles	Fan Diameter	1	2 inch / 07 cm		2 inch / 32 cm	60 inch 152 cn	
	RPM (Low / High)				/ 212	51 / 152	70
	CFM (Low/High) Watts (High)			-	.49	1783 / 58 30.81	/ð
	CFM/Watt (High)	168		149		191	
	Blade Pitch			15°		15°	
shown in				OTO	METRICS		
Light Maple with 42" Walnut	Lamping (Re Remote Di				Integ	rated LED Yes	
blades	Delivered Temp					3075	
	Delivered		nens			690	
	CR Wat					90 16	
	Hou	rs					
	Light kit longe					27.4 Years	
shown in	<u> </u>	TAN	IDARD E				
shown in Barn Wood with 42" Barn Wood blades	Black 6-speed RF remote control with reverse	Light Cover White wireless Decora-style, 6-speed, wall control with reverse					
<b>U</b> us	NOTE: Only o	com	patible w	ith ir	cluded co		_
7" / 10 pm : 14th	Blade Options						
7" / 18 cm width	Barn Mati Wood Blac	e	Mat Whi		Walnu	t	35



shown in Matte Black with 42" Light Maple blades

### Irene-5

shown in Textured Bronze with 52" Walnut blades

hown in Textured Bronze with 52" Matte White blades

hown in Textured Bronze with 42" Matte Black blades

The Irene-5 is rustic, yet strikingly modern with five neatly joined, solid wood matte black, matte white, walnut, or barn wood tone blades. A spherical motor housing complements its minimal profile. Irene-5 is streamline while still appearing warm and natural. Constructed of cast aluminum and heavy stamped





ATLAS

	IRENE-5							
	FINIS	SH A	AND BLA	DE OPTION	IS			
	SK	U#		<b>XXX-XX</b> Finish+Blade	+Diameter)			
	Standa Finish		Matte B Textured	BK TB				
	Blade Finisł	nes	Barn Wo Gray As Light Ma Matte B Matte W Walnut	BW GA LM BK MWH WA				
	Fan Diame	ter	52 inche	es / 107 cm es / 132 cm es / 152 cm	42 52 60			
- Contractor		CHNICA						
	Fan Diamet	er		2, 52 or 60	150			
	Blade Mater		ers: 107, 132 c Solid Wood	or 152				
	Overall Dro				wnrod length			
	Fan Weig		12 Inche 18 lbs	5, 55 cm · 00				
	Downrods Lengt Field cuttab Non-thread		, 10, 20, 30, 4 ers: 13, 25, 51					
	Downrod Diameter		1 inch					
	Volta	ge	110 or 22	20				
	Motor Ty	ре	DC					
	Environme	ent	Damp locations for all finishes. Neither coastal, saltwater nor chlorine compatible.					
	Ambien	ce	Silent					
	Safety Certificati	on	ETL / CI	ETL				
	Warran							
	NEW JAN 21, 2		DOE MOTOR EFFICIENCY DATA					
	Fan Diameter		2 inch / 07 cm	52 inch / 132 cm	60 inch / 152 cm			
	RPM (Low/High)		/ 229	51 / 156	52 / 77			
and the second	CFM (Low / High)		2 / 4261	1784 / 5783	3328 / 5006			
	Watts (High) CFM/Watt (High)			32.18 179	31.38 175			
	Blade Pitch	150		179 15°	173 15°			
				QUIPMENT	-			
	-			inches / 25 cr	n			
				py for up to 3				
	6-speed RF remote control w/reverse in black			Vireless Decora-style, S-speed, wall control in white				
	NOTE: Only compatible with included controllers.							
6° / 15 c	m width	rn od	Options Gra Ash Matt	y Light Mapl	e			
	Mai Blae		Matt Whit	Waln	ut			

shown in Brushed Pewter with 60" Gray Ash blades

**FILLER** 

 shown in Polished Chrome with 42"Barn Wood blades

shown in Brushed Brass with 42" Walnut blades

shown in Walnut with 42" Barn Wood

blades

shown in Barn Wood with 42" Gray Ash blades

Matte Black with 42"Matte Black blades

**Blade Options** 

Barn

Wood

Matte

Black

Gray

Ash

Matte

White

shown in Gloss White with 52" Matte White blades

Light

Maple

Walnut

shown in Brushed Nickel with 52" Walnut blades

shown in Brushed Bronze with 42" Light Maple blades

shown in Light Maple with 42" Walnut blades

shown in Textured Bronze with 42" Walnut blade

· set the

Irene-5H

ATLAS

The Irene-5H ceiling-mount fan is rustic, yet strikingly modern with five neatly joined, solid wood, matte black, matte white, gray ash, light maple, walnut, or barn wood tone blades. A cylindrical motor housing complements its minimal profile. Irene-5H is streamline while still appearing warm and natural. Constructed of cast aluminum and heavy stamped steel, the Irene-5H has a limited lifetime warranty.





		R	EN	E-5H				
		_						
	SKI		IR5H-XXXX-XXX-XX (Model+Finish+Blade+Diameter)					
	Standard Finish	es	Barn Wo Brushec Brushec Brushec Gloss W Light Ma Matte B Polishec	Barn Wood Brushed Brass Brushed Bronze Brushed Nickel Brushed Pewter Gloss White Light Maple Matte Black Polished Chrome Textured Bronze Walnut				
	Blade Finishes		Barn Wo Gray As Light Ma Matte B Matte W Walnut	BW GA LM BK MWH WA				
	Fan Diame	ter	52 inche	es / 107 cm es / 132 cm es / 152 cm	42 52 60			
		TF	CHNICAL	-				
	Ex D'			12, 52 or 60				
	Fan Diamet	centime	ters: 107, 132 (	or 152				
	Blade Material			t Solid Wood s/25 cm				
	Overall Dro Fan Weig	· ·	10 Inche 12 lbs	5/25 CIII				
	Voltag		110 or 220					
	Motor Ty	-	DC					
	Environme		Damp locations for all finishes. Neither coastal, saltwater nor chlorine compatible.					
	Ambience		Silent					
	Safety Certificatio Warran		ETL / CETL Limited Lifetime					
		J						
	Fan Diameter	4	2 inch /	52 inch /	60 inch /			
-			07 cm / 226	132 cm 51 / 151	152 cm 51 / 78			
	RPM (Low / High) CFM (Low / High)		/ 226 5 / 3989	1631 / 4970	2201/3543			
	Watts (High)	25.		31.46	31.58			
	CFM/Watt (High)	193		162	123			
	Blade Pitch	15°		15°	15°			
	6-speed RF remote control w/reverse in black			QUIPMENT Wireless Decora-style, 5-speed, wall control in white	e			
	NOTE: Only o	com	patible wi	th included co	ontrollers.			
		7" / 1	8 cm	_				
	10" / 25 cm			C Us	6" / 15 cm width			
Blade Pitch 15		2",	/ 5 cm					
	42", 52" or 60" /	107 c	m, 132 cm o	r 152 cm	30			

shown in Gloss White with 60" walnut blades

shown in Brushed Bronze with 42" Matte Black bla

shown in Matte Black with 52" Matte Black blades

### Irene-5HLK

shown in Light Maple with 42" Matte White hlades

shown in Textured Bronze with 42" Walnut blades

shov

shown in Barn Wood with 52" Matte White lades

> shown in Brushed Nickel with 42" Barn Wood blades

shown in Polished Chrome with 60" Barn Wood blad



The Irene-5HLK ceiling-mount fan is rustic, yet strikingly modern with five neatly joined, solid wood matte black, matte white, walnut, or barn wood tone blades. A cylindrical motor housing complements its minimal profile. Irene-5HLK is streamline while still appearing warm and natural. Constructed of cast aluminum and heavy stamped steel, the Irene-5HLK has a limited lifetime warranty.



ATLAS

	IRENE-5HLK							
	FINIS	ΗA	ND BLA	DE	OPTION	S		
	SKU	J#			XX-XXX-			
	Standard Finish	es	Barn Wood Brushed Brass Brushed Bronze Brushed Nickel Brushed Pewter Light Maple Gloss White Matte Black Polished Chrome Textured Bronze			+Diameter) BW BRBR BB BN BP LM WH BK CR TB		
shown in Brushed Pewter with 42" Matte Black blades	Blade Finishes		Walnut Barn Wood Tone Matte Black Matte White Walnut Tone 42 inches / 107 cm			WN BW BK MWH WA 42		
	Fan Diameter		52 inch 60 inch	es /	132 cm	52 60		
1000 1000		TE	CHNICAL					
	Fan Diamet	_	inches:	42, !	52 or 60 :: 107, 132	or 152		
AND ST.	Blade Mater	CNC Cu	t So	lid Wood				
	Overall Dro		12 inche	s/3	0 cm			
	Fan Weight		13 lbs	20				
shown in Walnut with	Voltag Motor Typ	-	110 or 22 DC	20				
42" Walnut blades	Environment		Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible					
	Ambien	Silent	0	Ilpatible				
	Safety Certification	ETL / C	ETL					
	Warran	Limited		time				
	NEW JAN 21, 20	020	DOE MC	то	REFFICIE	ENCY DATA		
0	Fan Diameter		2 inch / 07 cm		2 inch / 32 cm	60 inch / 152 cm		
shown in Brushed Brass with	RPM (Low / High)				/ 179	51 / 88		
42" Matte White blades	CFM (Low / High) Watts (High)				2 / 4749 12	2116 / 3660 30.78		
	CFM/Watt (High)	127			)	132		
	Blade Pitch	15°		15°		15°		
		ΗT	KIT PHOTOMETR					
	Lamping (Re					Integrated LED		
- ANT	Remote Di					Yes		
	Delivered Temp					3075		
sala	Delivered CR	-	nens			690 90		
	CR Wat					16		
	Hou				6	0,000		
	Light kit longevity if used 6 Hours/Day: 27.4 Yea					27.4 Years		
	STANDARD EQUIPMENT							
			Light Co	over				
6* / 15 cm width	6-speed RF remote control w/reverse in black	Wireless Decora-style, 6-speed, wall control in white						
	NOTE: Only c	omp	oatible wit	th in	cluded co	ntrollers.		
	Blade Option Barn Wood Blac	te	Mat Whi		Walne	ut 41		



	KAYE					
FINISH /	AND BLADE OPTIONS					
SKU#	кс-хх					
Finishes	(Model+Finish)Brushed NickelBNMatte BlackBKPolished ChromeCRTextured BronzeTBGloss WhiteWH					
TE	CHNICAL SPECS					
Fan Weight	10.5 lbs					
Blade Material	Metal / ABS					
Voltage	110 or 220					
Motor Type	AC					
Oscillation	Yes					
Fan Diameter	13 inches / 33 cm					
Fan Height	13 inches / 33 cm					
Fan Projection	17.5 inches / 44 cm					
Ceiling Mount Overall Drop	17.5 inches / 44 cm					
Recommended	Approximately 24 inches /					
Mounting Height	61 cm from ceiling					
Fan Guard	Safety Cage					
Blade Pitch	31°					
Environment	Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible					
Ambience	Soothing White Noise					
Safety Certification	ETL / CETL					
Warranty	Limited Lifetime					
NEW JAN 21, 2020	0 DOE MOTOR EFFICIENCY DATA					
RPM (Low / High)	1213 / 1445					
CFM (Low / High)	868 / 1303					
Watts (High)	47.68					
CFM/Watt (High)	29					
Blade Pitch	31° NDARD EQUIPMENT					
	Safety cage					
Side-m	nounted wall junction box					
	ACCESSORY					
White Decora- style, 3-speed wall control	Black 3-speed RF remote control					
mechanism independent 2) The remote contro	n is needed to operate the oscillation ndent of the fan blades. I receiver will not fit behind the wall ectrician will need to hide the receiver cording to code.					







# Laura



The Laura 3-speed, left-to-right 90 degree oscillating wall fan offers the best in function. Its patented design boasts a whisper-quiet DC motor, remote control operation and easy 2-wire installation. Compact and powerful, Laura can be mounted in small, awkward spaces or in front of HVAC ducts to improve the efficiency of heating, ventilation or air conditioning. Constructed of cast aluminum and heavy stamped steel, Laura carries a limited lifetime warranty.











LAURA						
FINISH /	AND BLADE OPTIONS					
SKU#	LL-XX (Model+Finish)					
Finishes	Brushed NickelBNMatte BlackBKTextured BronzeTB					
TE	ECHNICAL SPECS					
Fan Weight	12 lbs					
Blade Material	Metal / ABS					
Voltage	110 - 240					
Motor Type	DC					
Oscillation	Yes					
Fan Diameter	16 inches / 41 cm					
Fan Height	14.5 inches / 37 cm					
Fan Projection	19.5 inches / 50 cm					
Recommended Mounting Height	Approximately 24 inches / 61 cm from ceiling					
Fan Guard	Safety Cage					
Environment	Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible					
Ambience	Soothing White Noise					
Safety Certification	UL / CUL					
Warranty	Limited Lifetime					
NEW JAN 21, 2020	D DOE MOTOR EFFICIENCY DATA					
RPM (Low / High)	1231 / 1520					
CFM (Low / High)	1056 / 1600					
Watts (High)	28.1					
CFM/Watt (High)	56.94					
Blade Pitch	31°					
STAN	NDARD EQUIPMENT					
Safety ca	ge					
Side-mounted wall	junction box					
Black 3-speed RF re	emote control					
Note: 1) Two-wire system re operate the oscillat independent of the Three-wire system i 2) Receiver already hi canopy.	ion mechanism e fan blades. not needed.					



options are barn wood, matte black, matte white or walnut. Constructed of cast aluminum and heavy stamped steel, Lindsay carries a limited lifetime warranty.









The oscillating Melody, 3-speed wall-mounted fan, designed in the Art Nouveau style with a grand, arching gooseneck, provides maximum multi-directional airflow with its 90° left to right sweep. Melody can be mounted in small, awkward spaces or in front of HVAC ducts to improve the efficiency of the heating, ventilation or air conditioning of any space. Constructed of cast aluminum and heavy stamped steel, the Melody carries a limited lifetime warranty.







### MELODY

FINISH /	AND BLADE OPTIONS
SKU#	<b>ME-XX</b> (Model+Finish)
Finishes	Matte Black BK Textured Bronze TB
ТЕ	CHNICAL SPECS
Fan Weight	14 lbs
Blade Material	Metal / ABS
Voltage	110 or 220
Motor Type	AC
Oscillation	Yes
Fan Diameter	13 inches / 33 cm
Fan Height	20 inches / 51 cm
Fan Projection	20 inches / 51 cm
Recommended Mounting Height	Approximately 24 inches / 61 cm from ceiling
Fan Guard	Safety Cage
Environment	Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible
Ambience	Soothing White Noise
Safety Certification	ETL / CETL
Warranty	Limited Lifetime
NEW JAN 21, 2020	D DOE MOTOR EFFICIENCY DATA
RPM (Low / High)	1213 / 1495
CFM (Low / High)	868 / 1303
Watts (High)	47.68
CFM/Watt (High)	27.32
Blade Pitch	31°
STAN	NDARD EQUIPMENT
	Safety cage
Side-m	nounted wall junction box
Decora-style, 3-speed wall control in white	ACCESSORY Black 3-speed RF remote control
	n is needed to operate the oscillation ndent of the fan blades.

mechanism independent of the fan blades.2) The remote control receiver will not fit behind the wall canopy. A clever electrician will need to hide the receiver in wall or ceiling according to code.

49



Designed by Chicago architect Stephen Katz in 2018, the Molly ceiling fan combines modern organic geometry with outstanding performance and function. The blade shape was developed using advanced computer software which allowed the design to achieve a complex form. The result is a clean, natural and contemporary look perfect for any room or décor. Available in gloss white or matte black finish, Molly will complement a variety of design styles while also providing a fresh and unique, modern statement. Constructed of cast aluminum and heavy stamped steel, the Molly carries a limited lifetime warranty.





shown in Gloss White

	M	IOLLY
	FINISH A	ND BLADE OPTIONS
	SKU#	<b>MK-XX</b> (Model+Finish)
	Standard Finishes	Gloss White WH Matte Black BK
		CHNICAL SPECS
	Fan Diameter	56 inches / 142 cm
	Blade Material	ABS
	Overall Drop	12 inches/30 cm+downrod length
	Fan Weight	17 lbs
	Voltage	110 (Please contact us for 220V)
	Motor Type	DC
	Downrods Lengths Field cuttable, non-threaded	inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183
	Downrod Diameter	1 inch
	Environment	Wet locations for all finishes All weather blade system. Neither coastal, saltwater nor chlorine compatible
	Ambience	Silent
	Safety Certification	ETL / CETL
	Warranty	Limited Lifetime
	NEW JAN 21, 2020	DOE MOTOR EFFICIENCY DATA
	RPM (Low / High)	49 / 116
	CFM (Low / High)	1556 / 3530
	Watts (High)	29.96
	CFM/Watt (High)	126
	Blade Pitch	45°
	STANI	DARD EQUIPMENT
	One down	rod of 10 inches / 25 cm
/ 5 cm width	Vaulted cei	ling canopy for up to 30°
	Black 6-speed RF remote control with reverse	White wireless Decora-style, 6-speed, wall control
	NOTE: Only comp	atible with included controllers.

shown in Matte Black with 52" Barn Wood blades

## Mollywood

Designed by Chicago architect Stephen Katz in 2018, the Mollywood ceiling fan combines modern organic geometry with outstanding performance and function. The blade shape was developed using advanced computer software which allowed the design to achieve a complex form. The result is a clean, natural and contemporary look perfect for any room or décor. Available in matte black, matte white, or textured bronze finishes with either barn wood, matte black, matte white or walnut tone solid wood blade options. Mollywood will complement a variety of design styles while also providing a fresh and unique, modern statement. Constructed of cast aluminum and heavy stamped steel, Mollywood carries a limited lifetime warranty.

Product Features

ТŶ

42", 52" or 60" / 107 cm, 132 cm or 152 cm

shown in Matte Black with 52" Matte Black blades

shown in Textured Bronze with 60" Walnut blades

shown in Brushed Brass with 52" Barn Wood blades

2" / 5 cm

10" / 25 cm

Downrods available in inches: 5, 10, 20, 30, 48 or 72

centimeters: 13, 25, 51, 76, 122, or 183

shown in Matte White with 42" Matte White blades

6" / <u>15 cm</u>

52

E DC5

DC

ATLAS

	MO	)L	.LY	WOC	D			
				ADE OPTION				
2	SKI	J#	<b>MW-XXX-XXX-XX</b> (Model+Finish+Blade+Diameter)					
	Standard Finish	Brushed Matte E Matte V Texture	BRBR BK MWH TB					
	Blade Fin	ish	Barn W Matte E Matte V Walnut	BW BK MWH WA				
e White e White blades	Fan Diame	ter	42 inch 52 inch 60 inch	42 52 60				
		ΤE	CHNICA	L SPECS				
	Fan Diamet	er		42, 52 or 60 eters: 107, 132	or 152			
	Blade Mater	ial		t Solid Wood				
Blade Options	Overall Dro	эр	12 inche	s / 30 cm + do	wnrod length			
	Fan Weig	ht	18 lbs					
Barn Wood Walnut	Downrods Lengt Field cuttab Non-threade	inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183						
	Downrod Diamet	1 inch						
	Voltag	110 (Contact us for 220 conversion)						
Matte Matte Black White	Motor Ty	DC						
DIACK	Environme	Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible						
	Ambien	се	Silent					
	Safety Certification	on	ETL / CETL					
	Warran	ty	Limited Lifetime					
	NEW JAN 21, 2	020	DOE MOTOR EFFICIENCY DATA					
	Fan Diameter		2 inch / 07 cm	52 inch / 132 cm	60 inch / 152 cm			
	RPM (Low/High)			51 / 129	52 / 103			
	CFM (Low/High)				658 / 2914			
	Watts (High)			31.60	34.35			
and the second second	CFM/Watt (High) Blade Pitch	84 45		88 45°	83 45°			
	STANDARD EQUIPMENT One downrod of 10 inches / 25 cm							
and the second second				ppy for up to $\frac{3}{2}$				
			Light c					
cm					U			
	Black 6-speed RF remote control with reverse	~		White wireless Decora-style, 6-speed, wall control				
	NOTE: Only o	om	oatible w	th included co				
2" / 5 cm w Blade Pitch 45	vidth							

shown in Matte White with 52" Walnut blades

Nan

Designed by Chicago architect Stephen Katz, the Nan ceiling fan is a contemporary take on traditional fan design with superior performance and functionality. The Nan fan feels at home in any room or setting from casual to formal and everything in between. This timeless ceiling fan works in residential environments, restaurants, hospitality or even office settings. The Nan fan has the perfect amount of design presence for any size room or season. The fully adjustable fan motor speeds makes moving the right amount of air simple and easy. The Nan fan will feel like a natural part of the room and enhance any space with a fresh

breeze. Also available is the larger Nan XL for larger spaces. Product Features

Ŕ **N ₽** DC<sup>5</sup> Damp Locatior DC Motor Remote Control Wall Control Silent

alter to wanter

shown in Matte White with 42" Matte White blades

shown in Textured Bronze

shown in Brushed Brass

with 42" Gray

Ash blad

shown in

Textured Bronze with 52" Light

Maple blade

with 52" Walnut blades

shown in Matte White with 52" Barn Wood blades

shown in Matte Black vith 60" Walnut blades





			NA	N					
	FINISH AND BLADE OPTIONS								
	NK-XXX-XXX-XX								
	SKI	J#		Finish+Blade					
	Standard Finish	Brushed Matte B Matte V Texture	lack	BRBR BK MWH TB					
shown in Matte Black with 42" Matte Black blades	Blade Fin	ish	Barn Wo Gray As Light M Matte B Matte V Walnut	h aple lack	BW GA LM BK MWH WA				
	Fan Diame	ter	52 inch	es / 107 cm es / 132 cm es / 152 cm	42 52 60				
		ΤE	CHNICA	L SPECS					
	Fan Diamet	er		2, 52 or 60					
				ters: 107, 132 (					
vn in hed Brass	Blade Mater	-		t Solid Wood s/30 cm + do					
42" Matte	Overall Dro Fan Weig	12 Inche 18 lbs	s/ 30 cm + u0	whrod length					
k blades	Downrods Lengt Field cuttab Non-threade	hs <i>le.</i>	inches: 5	5, 10, 20, 30, 4 ters: 13, 25, 5	8, 72 1, 76, 122, 183				
	Downrod Diamet	1 inch							
	Voltag	-	tact us for 22	0 conversion)					
	Motor Typ	DC							
	Environme	nt	Neither	ocations for a coastal, saltv compatible					
	Ambien	ce	Silent						
	Safety Certification	on	ETL / C	ETL					
	Warran	ty	Limited Lifetime						
	NEW JAN 21, 20			DTOR EFFICI	ENCY DATA				
	Fan Diameter		2 inch / 07 cm	52 inch / 132 cm	60 inch / 152 cm				
	RPM (Low/High)		/ 235	51 / 202	51 / 152				
	CFM (Low/High)		1 / 5101	1692 / 7389	2454 / 8251				
	Watts (High)	20		32.61	32.58				
	CFM/Watt (High)	213		220	256				
	Blade Pitch	15°			15°				
				QUIPMENT					
				inches / 25 cr					
	Black 6-speed RF remote control with reverse			White wireless Decora-style, S-speed, wall control	() () () () () () () () () () () () () (				
					Ð				
	NOTE: Only c	om	oatible wi	th included co	ontrollers.				
5 cm width		de arn	Optio	ns <sup>.</sup> ay Lig	ht				





NARN XLL         FINISH AND BLADE OPTIONS         SKU#       NKXL-XX-XX-XX (Model Finish+Blade-Diameter)         Standard Finishes         Black       BRRR Black         Black This He Brass Black       BRRR Black         Black Finish Hate White With Walnut         TechNICAL SPECE         Fan Diameter       72 inches / 183 cm       72         Blade Finish         Mothes: 72 or 90 conthes/ 229 cm       90         OPTICEL SPECE         Fan Diameter       inches: 72 or 90 conthes/ 720 rm         OPTICEL SPECE         Fan Diameter       inches: 72 or 90 conthes/ 720 rm         OPTICEL SPECE         Fan Diameter       inches: 72 or 90 conthes/ 720 cm         OPTICEL SPECE         Pan Diameter       inches: 51,02,030, 48,72 centimeters: 13, 25, 51, 76, 122, 183         Downrod Liendse         Non-threaded         Downrod Stends         Inches: S1,02,030, 48,72 centimeters: 13, 25, 51, 76, 122, 183         Downrod					/ 1			
SKU#       NKXL-XXX-XX (Model+Finish+Bilade+Diameter)         Standard Finishes       Brushed Brass Black       BRBR Black         Standard Finishes       Barn Wood Gray Ash Light Maple       DK Mute White       MWH Gray Ash Light Maple         Blade Finish       Bare Wood Gray Ash Light Maple       DK Mute White       MWH WH WH Walnut         Fan Diameter       72 inches / 183 cm 90 inches / 229 cm       70         CHICAL SPECS       Fan Diameter       Inches: 72 or 90 centimeters: 183 or 229         Blade Material       CNC Cut Solid Wood       Overall Drop 20 inches / 229 cm         Overall Drop       12 inches/30 cm + downrod length Fan Weight 19 lbs         Downrod Langths Field cuttable       Inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183         Downrod Diameter       1 inch         Voltage 110 (Contact us for 220 conversion)         Motor Type       DC         Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible         Ambience       Silent         Safety Certification       ETL / CETL         Warrarty       Limited Lifetime         INDUSTRIAL CELLING FAN ESTIMATED EFFICIENCY DATA Fan Diameter       72 inch / 183 cm         One downrod of 10 inches / 25 cm       Valled ceiling canopy for up to 30°         CFM (Low / High)       339		Γ						
Standard Finishes       Brushed Brass       BRBR         Standard Finishes       Black       BK         Matte White       MWH         Black       BK         Matte White       MWH         Blade Finish       Blade Finish         Blade Finish       Blade Stars         Blade Finish       Blade Stars         Blade Finish       Blade Stars         Blade Finish       Blade Stars         Matte White       MWH         Walt       Walt         Fan Diameter       72 inches / 183 cm         Join ches / 229 cm       90         Fan Diameter       12 inches / 30 cm + downrod length         Fan Weight       19 lbs         Downrod Lengths       inches: 5, 10, 20, 30, 48, 72         entimeters: 13, 25, 51, 76, 122, 183       Downrod lengths         Not-threaded       110 (Contact us for 220 conversion)         Motor Type       DC         Damp locations for all finishes         Neither coasti, saltwater nor chlorine compatible         Ambience       Silent         Safety Certification       ETL / CETL         Warranty       Limited Lifetime         INDUSTRIAL CELLING FAN ESTIMATED EFFICIENCY DATA         Fan Diameter								
Standard Finishes       Black Matte White Textured Bronze       BK Matte White Textured Bronze       BK Matte White MWH MWH MWH Matte Black       BW GA Light Maple         Blade Finish       Blade Finish       Batte Black Matte White Matte Black       BK Matte White MWH Wahut       BK Matte White MWH Wahut         Fan Diameter       72 inches / 183 cm 90 inches / 229 cm 90       72 90 inches / 229 cm 90       72 90 inches / 229 cm 90         Blade Material       CNC Cut Solid Wood       Overall Drop 12 inches / 30 cm + downrod length         Fan Weight       19 lbs       Downrods Lengths Field cutable Non-threaded centimeters: 13, 25, 51, 76, 122, 183         Downrod Diameter       1 inch       Downrod Diameter         Voltage       110 (Contact us for 220 conversion)         Motor Type       DC         Damp locations for all finishes Neither costal, saltwater nor chlorine compatible         Ambience       Silent         Safety Certification       ETL / CETL         Warrarty       Limited Lifetime         INDUSTRIAL CELING FAN ESTIMATED EFFICIENCY DATA         Fan Diameter       72 inch / 183 cm       90 inch / 229 cm         RPM (Low/High)       3727 / 11,302       4257 / 13,687         Watts (High)       329       456         Blade Pitch       15°       15°         Blade Pitch <th>SKU</th> <th>J#</th> <th>(Mode</th> <th>el+Finish-</th> <th></th> <th>· ·</th>	SKU	J#	(Mode	el+Finish-		· ·		
Gray Ash Biade Finish Biade Finish Hatte Black Matte White Matte White MWH Walnut Fan Diameter Fan Diameter Fan Diameter Fan Diameter Fan Diameter Fan Diameter Fan Diameter Fan Weight Downrod Lengths Field cuttable Non-threaded Downrod Lengths Field cuttable Non-threaded Downrod Stattable Fan Veight Downrod Stattable Fan Weight Downrod Stattable Field cuttable Non-threaded Downrod Stattable Field cuttable Stattable Downrod Stattable Field cuttable Field cuttable Stattable Downrod Stattable Field cuttable Stattable Downrod Stattable Field cuttable Stattable Downrod Stattable Downrod Stattable Downrod Stattable Field cuttable Stattable Downrod Stattable Downrod Stattable Stattabl	Standard Finish	Standard Finishes			Black Matte White			
Fan Diameter       90 inches / 229 cm       90         TECHNICAL SPECS         Fan Diameter       inches: 72 or 90 centimeters: 183 or 229         Blade Material       CNC Cut Solid Wood         Overall Drop       12 inches / 30 cm + downrod length         Fan Weight       19 lbs         Downrod Lengths       inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183         Downrod Diameter       1 inch         Voltage       110 (Contact us for 220 conversion)         Motor Type       DC         Damp locations for all finishes         Neither coastal, saltwater nor chlorine compatible         Ambience       Silent         Safety Certification       ETL / CETL         Warranty       Limited Lifetime         INDUSTRIAL CELLING FAN ESTIMATED EFFICIENCY DATA         Fan Diameter       72 inch / 183 cm       90 inch / 229 cm         RPM (Low/High)       48 / 86       28 / 143         CFM (Low/High)       3727 / 11,302       4257 / 13,687         Watts (High)       339       456         Black Pitch       15°       15°         STANDARD EOUIPMENT         One downrod of 10 inches / 25 cm         Vaulted ceiling canopy for up to 30°         B	Blade Fin	ish	Gray A Light Matte Matte	Ash Maple Black White		GA LM BK MWH		
TECHNICAL SPECS         Fan Diameter       inches: 72 or 90 centimeters: 183 or 229         Blade Material       CNC Cut Solid Wood         Overall Drop       12 inches/30 cm + downrod length         Fan Weight       19 lbs         Downrods Lengths Field cuttable       inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183         Downrod Diameter       1 inch         Voltage       110 (Contact us for 220 conversion)         Motor Type       DC         Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible         Ambience       Silent         Safety Certification       ETL / CETL         Warranty       Limited Lifetime         INDUSTRIAL CellING FAN ESTIMATED EFFICIENCY DATA         Fan Diameter       72 inch / 183 cm       90 inch / 229 cm         RPM (Low/High)       3727 / 11,302       4257 / 13,687         Watts (High)       329       456         Blade Pitch 15°       15°       5         STANDARD EQUPMENT       One downrod of 10 inches / 25 cm         Vaulted ceiling canopy for up to 30°       Standa control         Black 6-speed RF remote control with reverse       Gray       Light Matter         Wood       Gray       Light Matter       Light Matter	Fan Diame	ter						
Blade Material CNC Cut Solid Wood Overall Drop 12 inches/30 cm + downrod length Fan Weight 19 lbs Downrods Lengths Field cuttable. Non-threaded Downrod Diameter 1 inch Voltage 110 (Contact us for 220 conversion) Motor Type DC Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible Ambience Silent Safety Certification ETL / CETL Warranty Limited Lifetime INDUSTRIAL CEILING FAN ESTIMATED EFFICIENCY DATA Fan Diameter 72 inch / 183 cm 90 inch / 229 cm RPM (Low / High) 48 / 86 28 / 143 CFM (Low / High) 3727 / 11,302 4257 / 13,687 Watts (High) 36.08 31.59 CFM/Watt (High) 339 456 Blade Pitch 15° 15° STANDARD EQUIPMENT One downrod of 10 inches / 25 cm Vaulted ceiling canopy for up to 30° NoTE: Only compatible with included controllers. Black 6-speed RF remote control with reverse NOTE: Only compatible with included controllers. Black 0-speed RF remote control Motter Back Motte Black 0-speed RF remote control Motter Black 6'/ 15 cm width Motte Mote M		Т				50		
Overall Drop       12 inches / 30 cm + downrod length         Fan Weight       19 lbs         Downrods Lengths Field cuttable Non-threaded       inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183         Downrod Diameter       1 inch         Voltage       110 (Contact us for 220 conversion)         Motor Type       DC         Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible         Ambience       Silent         Safety Certification       ETL / CETL         Warranty       Limited Lifetime         INDUSTRIAL CELLING FAN ESTIMATED EFFICIENCY DATA         Fan Diameter       72 inch / 183 cm       90 inch / 229 cm         RPM (Low/High)       48 / 86       28 / 143         CFM (Low/High)       3727 / 11,302       4257 / 13,687         Watts (High)       339       456         Blade Pitch       15°       15°         STANDARD EQUIPMENT       One downrod of 10 inches / 25 cm         Vaulted ceiling canopy for up to 30°       Valted ceiling canopy for up to 30°         Black 6-speed RF remote control with reverse       Gray Wolte wireless 6-speed, wall control       Light Maghe         42.0r 183       Barn       Gray Wolte       Light Maghe         6' / 15 cm width       Mafte Black	Fan Diamet	er						
Fan Weight       19 lbs         Downrods Lengths Field cuttable Non-threaded       inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183         Downrod Diameter       1 inch         Voltage       110 (Contact us for 220 conversion)         Motor Type       DC         Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible         Ambience       Silent         Safety Certification       ETL / CETL         Warranty       Limited Lifetime         INDUSTRIAL CELLING FAN ESTIMATED EFFICIENCY DATA         Fan Diameter       72 inch / 183 cm       90 inch / 229 cm         RPM (Low/High)       36.08       31.59         CFM (Low/High)       3727 / 11,302       4257 / 13,687         Watts (High)       339       456         Blade Pitch       15°       15°         STANDARD EQUIPMENT       One downrod of 10 inches / 25 cm         Vaulted ceiling canopy for up to 30°       Vaulted ceiling canopy for up to 30°         Elack 6-speed RF remote control with reverse       Gray Wood       Light Mash         Matte Wood       Matte White       Light Maple         6' / 15 cm width       Matte Barn       Matte White       Wolnut	Blade Mater	ial	CNC C	Cut Solid	Wood			
Downrods Lengths Field cuttable. Non-threaded Downrod Diameter 1 inch Voltage 110 (Contact us for 220 conversion) Motor Type DC Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible Ambience Silent Safety Certification ETL / CETL Warranty Limited Lifetime INDUSTRIAL CELLING FAN ESTIMATED EFFICIENCY DATA Fan Diameter 72 inch / 183 cm 90 inch / 229 cm RPM (Low/High) 36.08 31.59 CFM/Watt (High) 3727 / 11,302 4257 / 13,687 Watts (High) 36.08 31.59 CFM/Watt (High) 339 456 Blade Pitch 15° 15° STANDARD EQUIPMENT One downrod of 10 inches / 25 cm Vaulted ceiling canopy for up to 30° Black 6-speed RF with reverse Word Compatible with included controllers. Black Options 22. or 183 6' / 15 cm width Matte Barn Wood Matter Mat	Overall Dro	р	12 inch	nes/30 c	m + downro	od length		
Field cuttable Non-threaded       inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183         Downrod Diameter       1 inch         Voltage       110 (Contact us for 220 conversion)         Motor Type       DC         Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible         Ambience       Silent         Safety Certification       ETL / CETL         Warranty       Limited Lifetime         INDUSTRIAL CEILING FAN ESTIMATED EFFICIENCY DATA         Fan Diameter       72 inch / 183 cm       90 inch / 229 cm         RPM (Low/High)       48 / 86       28 / 143         CFM (Low/High)       3727 / 11,302       4257 / 13,687         Watts (High)       36.08       31.59         CFM/Watt (High)       33 9       456         Blade Pitch       15°       15°         STANDARD EOUIPMENT       One downrod of 10 inches / 25 cm         Vaulted ceiling canopy for up to 30°       Vaulted ceiling canopy for up to 30°         Black 6-speed RF remote control with reverse       White wireless Decora-style, 6-speed, wall control       Ight Maple         Motte       Barn       Gray Ash       Light Maple         Matte       Black Options       Light Maple			19 lbs					
Voltage       110 (Contact us for 220 conversion)         Motor Type       DC         Environment       Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible         Ambience       Silent         Safety Certification       ETL / CETL         Warranty       Limited Lifetime         INDUSTRIAL CEILING FAN ESTIMATED EFFICIENCY DATA         Fan Diameter       72 inch / 183 cm       90 inch / 229 cm         RPM (Low/High)       48 / 86       28 / 143         CFM (Low/High)       3727 / 11,302       4257 / 13,687         Watts (High)       36.08       31.59         CFM/Watt (High)       339       456         Blade Pitch       15°       15°         STANDARD EOUIPMENT       One downrod of 10 inches / 25 cm         Vaulted ceiling canopy for up to 30°       Vaulted ceiling canopy for up to 30°         Black 6-speed RF remote control with reverse       White wireless Decora-style, 6-speed, wall control       Image         NOTE: Only compatible with included controllers.       Blade Options       Image         42. or 183       Matte Black       Matte Black       Walnut	Field cuttab	le.						
Motor Type       DC         Environment       Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible         Ambience       Silent         Safety Certification       ETL / CETL         Warranty       Limited Lifetime         INDUSTRIAL CEILING FAN ESTIMATED EFFICIENCY DATA         Fan Diameter       72 inch / 183 cm       90 inch / 229 cm         RPM (Low /High)       48 / 86       28 / 143         CFM (Low /High)       3727 / 11,302       4257 / 13,687         Watts (High)       36.08       31.59         CFM/Watt (High)       339       456         Blade Pitch       15°       15°         STANDARD EQUIPMENT       One downrod of 10 inches / 25 cm         Vaulted ceiling canopy for up to 30°       Vaulted ceiling canopy for up to 30°         Black 6-speed RF remote control with reverse       White wireless Control       Image: Control for up to 30°         NOTE: Only compatible with included controllers.       Black Options       Image: Cray Ash       Light         6*/15 cm width       Matte Black       Matte White       Walnut	Downrod Diameter		1 inch					
Environment       Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible         Ambience       Silent         Safety Certification       ETL / CETL         Warranty       Limited Lifetime         INDUSTRIAL CEILING FAN ESTIMATED EFFICIENCY DATA         Fan Diameter       72 inch / 183 cm       90 inch / 229 cm         RPM (Low/High)       48 / 86       28 / 143         CFM (Low/High)       3727 / 11,302       4257 / 13,687         Watts (High)       36.08       31.59         CFM (Low/High)       339       456         Blade Pitch       15°       15°         STANDARD EQUIPMENT       One downrod of 10 inches / 25 cm       Vaulted ceiling canopy for up to 30°         Black 6-speed RF remote control with reverse       White wireless locar-style, 6-speed, wall control       10°         NOTE: Only compatible with included controllers.       Black Options       110°         Matte       Matte       Matte       Matte         Matte       Matte       Walnut       100		-						
Ambience Silent Safety Certification ETL / CETL Warranty Limited Lifetime INDUSTRIAL CEILING FAN ESTIMATED EFFICIENCY DATA Fan Diameter 72 inch / 183 cm 90 inch / 229 cm RPM (Low / High) 48 / 86 28 / 143 CFM (Low / High) 3727 / 11,302 4257 / 13,687 Watts (High) 36.08 31.59 CFM/Watt (High) 339 456 Blade Pitch 15° 15° STANDARD EQUIPMENT One downrod of 10 inches / 25 cm Vaulted ceiling canopy for up to 30° Black 6-speed RF remote control with reverse $Vaulted ceiling canopy for up to 30°$ Decora-style 6-speed, wall control NOTE: Only compatible with included controllers. Black 6-speed RF remote control White wireless Black Options 42. or 183 6' / 15 cm width Mathe Black 6' / 15 cm width			Damp locations for all finishes Neither coastal, saltwater nor chlorine					
Safety Certification ETL / CETL Warranty Limited Lifetime INDUSTRIAL CEILING FAN ESTIMATED EFFICIENCY DATA Fan Diameter 72 inch / 183 cm 90 inch / 229 cm RPM (Low / High) 48 / 86 28 / 143 CFM (Low / High) 3727 / 11,302 4257 / 13,687 Watts (High) 36.08 31.59 CFM/Watt (High) 339 456 Blade Pitch 15° 15° STANDARD EQUIPMENT One downrod of 10 inches / 25 cm Vaulted ceiling canopy for up to 30° Black 6-speed RF remote control with reverse Valled ceiling canopy for up to 30° NOTE: Only compatible with included controllers. Black 6-speed RF remote control White wireless becora-style 6' / 15 cm width 4 Mathe Black Mathe Walnut Mathe Mathe Walnut	Ambien	re						
Warranty       Limited Lifetime         INDUSTRIAL CEILING FAN ESTIMATED EFFICIENCY DATA         Fan Diameter       72 inch / 183 cm       90 inch / 229 cm         RPM (Low /High)       48 / 86       28 / 143         CFM (Low /High)       3727 / 11,302       4257 / 13,687         Watts (High)       3727 / 11,302       4257 / 13,687         Watts (High)       36.08       31.59         CFM/Watt (High)       339       456         Blade Pitch       15°       15°         STANDARD EQUIPMENT         One downrod of 10 inches / 25 cm         Vaulted ceiling canopy for up to 30°         Black 6-speed RF remote control with reverse       White wireless Decora-style, 6-speed, wall control         With reverse       Wood       Gray Mathematical Controllers.         Black 6-speed RF with reverse       Barn       Kash         Matter       Matter       Matter         % Yoolnut       Matter       Wolnut				CETL				
Fan Diameter       72 inch / 183 cm       90 inch / 229 cm         RPM (Low/High)       48 / 86       28 / 143         CFM (Low/High)       3727 / 11,302       4257 / 13,687         Watts (High)       36.08       31.59         CFM/Watt (High)       339       456         Blade Pitch       15°       15°         STANDARD EQUIPMENT         One downrod of 10 inches / 25 cm         Vaulted ceiling canopy for up to 30°         Black 6-speed RF remote control with reverse       White wireless Decora-style, 6-speed, wall control         with reverse       White with included controllers.         NOTE: Only compatible with included controllers.         Black 6'remote dots on the included controllers.         Motter       Matter         Wordnut       Matter         Wordnut       Matter         Wordnut       Matter			Limited Lifetime					
RPM (Low/High) 48 / 86 28 / 143 CFM (Low/High) 3727 / 11,302 4257 / 13,687 Watts (High) 36.08 31.59 CFM/Watt (High) 339 456 Blade Pitch 15° 15° STANDARD EQUIPMENT One downrod of 10 inches / 25 cm Vaulted ceiling canopy for up to 30° Black 6-speed RF remote control with reverse $Vaulted ceiling canopy for up to 30°$ NOTE: Only compatible with included controllers. Black 6-speed RF remote control NOTE: Only compatible with included controllers. Black 0-speed RF Provide Control with included controllers. Black 6-speed RF remote control NOTE: Only compatible with included controllers. Black 0-speed Matte Black 0-speed RF Walnut Matte Walnut	INDUSTRIAL CEI	LIN	G FAN ESTIMATED EFFICIENCY DATA					
CFM (Low/High) 3727 / 11,302 4257 / 13,687 Watts (High) 36.08 31.59 CFM/Watt (High) 339 456 Blade Pitch 15° 15° STANDARD EQUIPMENT One downrod of 10 inches / 25 cm Vaulted ceiling canopy for up to 30° Black 6-speed RF remote control with reverse With reverse White wireless Decora-style, 6-speed, wall control NOTE: Only compatible with included controllers. Blade Options 42, or 183 6' / 15 cm width Matter Black Matter Walnut	Fan Diameter	72	2 inch /	183 cm	90 incł	n / 229 cm		
Watts (High)       36.08       31.59         CFM/Watt (High)       339       456         Blade Pitch       15°       15°         STANDARD EQUIPMENT         One downrod of 10 inches / 25 cm         Vaulted ceiling canopy for up to 30°         Black 6-speed RF remote control with reverse       White wireless Decora-style, 6-speed, wall control         NOTE: Only compatible with included controllers.         Black 6' 15 cm width       Matte Black         6' / 15 cm width       Matte Black	RPM (Low/High)	48	3 / 86		28 / 143			
CFM/Watt (High) 339 456 Blade Pitch 15° 15° STANDARD EQUIPMENT One downrod of 10 inches / 25 cm Vaulted ceiling canopy for up to 30° Black 6-speed RF remote control with reverse $V$ $V$ White wireless Decora-style, 6-speed, wall control NOTE: Only compatible with included controllers. Black Options V Matte White $V$ Matte White $V$ Matte White $V$ Matte				302		,687		
Blade Pitch 15° 15° STANDARD EQUIPMENT One downrod of 10 inches / 25 cm Vaulted ceiling canopy for up to 30° Black 6-speed RF remote control with reverse RF White wireless Decora-style, 6-speed, wall ontrol NOTE: Only compatible with included controllers. Blade Options Barn Wood Gray Ash Light Matte Matte Walnut	 							
STANDARD EQUIPMENT         One downrod of 10 inches / 25 cm         Vaulted ceiling canopy for up to 30°         Black 6-speed RF remote control with reverse       Image: Control with reverse       Image: Control with reverse       Image: Control with reverse         NOTE: Only compatible with included controllers.       Image: Control with reverse       Image: Control with reverse       Image: Control with reverse         NOTE: Only compatible with included controllers.       Image: Control with reverse       Image: Control with reverse         1       Image: Control with reverse       Image: Control with reverse       Image: Control with reverse         1       Image: Control with reverse       Image: Control with reverse       Image: Control with reverse         1       Image: Control with reverse       Image: Control with reverse       Image: Control with reverse         1       Image: Control with reverse       Image: Control with reverse       Image: Control with reverse         1       Image: Control with reverse       Image: Control with reverse       Image: Control with reverse         1       Image: Control with reverse       Image: Control with reverse       Image: Control with reverse         1       Image: Control with reverse       Image: Control with reverse       Image: Control with reverse         12.000000000000000000000000000000000000								
One downrod of 10 inches / 25 cm Vaulted ceiling canopy for up to 30° Black 6-speed RF remote control with reverse Provide Control Provide Control NOTE: Only compatible with included controllers. Black Options Cray Ash Light Matte Black Matte White Winter Control								
Vaulted ceiling canopy for up to 30° Black 6-speed RF remote control with reverse White wireless Decora-style, 6-speed, wall control NOTE: Only compatible with included controllers. Blade Options Blade Options Cray Ash Light Matte Black Matte Walnut								
Black 6-speed RF remote control with reverse NOTE: Only compatible with included controllers. Black Options Barn Wood Gray Ash Light Matte Black Matte White Winte Walnut								
Blade Options Barn Wood Gray Light Maple  6" / 15 cm width  Matte Black Matte White Walnut	remote control			Decora- 6-speed	style,			
22, or 183 6° / 15 cm width Matte Black Matte Walnut	NOTE: Only compatible with included controllers.							
		Bo Wo	irn bod	Gray Ash Matte	Мар	ut		

72" or 90" / 183 cm or 229 cm



	PA	۲/	ſRĺ	С	IA-	3	
	FINIS	5H <i>A</i>	AND BLA	ADE	OPTION	S	
	SKI	J#	<b>PA3-XX-XXX-XX</b> (Model+Finish+Blade+Diameter)				
	Standard Finish	es	Brushe Brushe Polishe Texture Gloss V Matte E	BRBR BN CR TB WH BK			
	Blade Finisł	nes	Barn W Matte E Matte V Walnut	Black Whit	e e	BW BK MWH WA	
	Fan Diame	ter	42 inches / 52 inches / 60 inches /		132 cm	42 52 60	
		ΤЕ	CHNICA	L SF	PECS		
	Fan Diamet	er		inches: 42, 52 or 60			
	Blade Mater				: 107, 132 lid Wood	or 152	
	Overall Dro	эр	14 inche	es/3	6 cm + dov	wnrod lengt	h
	Fan Weight		19 lbs				
	Downrods Lengths Field cuttable. Non-threaded		inches: 5, 10, 20, 30, 48, 72 centimeters: 13, 25, 51, 76, 122, 183				33
	Downrod Diamet	er	1 inch	1 inch			
	Voltage		110 or 220				
	Motor Ty	ре					
	Environment		Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible				
	Ambience		Silent				
ckel rn Wood	Safety Certification		ETL / C				
	Warran	Limited					
	NEW JAN 21, 20		2 inch /		2 inch /	60 inch /	
and the second second	Fan Diameter	1	07 cm		132 cm	152 cm	
	RPM (Low / High)		/ 232	-	/ 219	51 / 156	
	CFM (Low / High)		0 / 4286		33 / 6077	2113 / 683	3
	Watts (High) CFM/Watt (High)	16. 211			.03	31.72 219	
	Blade Pitch	15°		15		15°	$\neg$
ons				-	METRICS		
	Lamping (Re	plac	ceable)		Integ	rated LED	
Matte	Remote Di					Yes	
Black	Delivered Temp					3075	
	Delivered CR	-	iens			690 90	-
14 14 14	Wat					16	$\neg$
Valnut	Hou				6	0,000	
	Light kit longe					27.4 Years	
			IDARD E				
					hes / 25 c		
3	Vaulteo	d ce	iling cand Light c		for up to 3	υ°	
cm width	Black 6-speed RF remote control with reverse			Whit Deco 6-sp	ce wireless bra-style, eed, control		
4	NOTE: Only c	om	oatible w	ith ir	ncluded co	ontrollers.	



42", 52" or 60" / 107 cm, 132 cm or 152 cm

	PATRÍCIA-5							
	FINIC				OPTION	c		
	SKU		PA5-XX	(-XX	x-xx			
	Standard Finish		(Model- Brushed Brushed Polished Texture Gloss W Matte B	d Bra d Nic d Ch d Br /hite	ass ckel irome onze	+Diameter) BRBR BN CR TB WH BK		
	Blade Finish	nes	Barn W Matte B Matte V Walnut	ood Slack Vhit	BK BK MWH WA			
	Fan Diame	ter	42 inches / 52 inches / 60 inches /		132 cm	42 52 60		
		TECHNICAL SPECS						
	Fan Diamet		inches:	42, 5	52 or 60	- n 150		
	Blade Mater	ial	centimeters: 107, 132 or 152ICNC Cut Solid Wood					
	Overall Dro	эр	14 inche	es / 3	6 cm + do	wnrod length		
	Fan Weig	19 lbs						
ons	Downrods Lengt Field cuttab Non-threade			), 20, 30, 4 s: 13, 25, 5	48, 72 1, 76, 122, 183			
	Downrod Diamet	er	1 inch					
Matte	Voltag	ge	110 or 220					
Black	Motor Typ	эе	DC					
	Environme		Damp locations for all finishes Neither coastal, saltwater nor chlorine compatible					
Valnut	Ambience		Silent					
	Safety Certification	on	ETL / CETL					
2011月出现了1	Warran	ty						
	NEW JAN 21, 20	020	DOE MO	ото	R EFFICI	ENCY DATA		
	Fan Diameter		2 inch / 107 cm		2 inch / 132 cm	60 inch / 152 cm		
	RPM (Low/High)	53	/ 221	51	/ 186	51/87		
	CFM (Low/High)	917	7 / 4386	139	98 / 5524	3247 / 5547		
	Watts (High)	30	.47	31.80		31.64		
	CFM/Watt (High)	137		170		194		
	Blade Pitch			15°		15°		
			KIT PHO	TO				
	Lamping (Re Remote Di				integ	rated LED Yes		
	Delivered Temp					3075		
	Delivered					690		
	CR					90		
	Wat	ts				16		
	Hou					0,000		
	Light kit longevity if used 6 Hours/Day: 27.4 Year							
	STANDARD EQUIPMENT One downrod of 10 inches / 25 cm							
					for up to 3			
			Light co					
2, or 183	Black 6-speed RF remote control with reverse	•		Whit Deco 6-sp	te wireless ora-style, eed, wall rol with			
						D		

shown in Matte Black with 52" Barn Wood blades

shown in Gloss White with 42" Matte White blades

shown in Brushed Nic with 52" Walnut blad

shown in Matte Black with 52" Matte Black blades

6" / 15 cm

# Super Janet



ATLAS



The Super Janet's remarkable design and solid construction in cast aluminum and heavy stamped steel make it the heroine in any commercial or residential space. Moving air with barely a whisper, its efficient DC motor turns solid wood blades in walnut, matte black, matte white, or barn wood tones. An ecoconscious LED light kit with light cover completes the package. Sophisticated, efficient and green, Super Janet carries a limited lifetime warranty.



shown in Textured Bronze with 60" Barn Wood blades

2" / 5 cm 4" / 10 cm width Downrods available in inches: 5, 10, 20, 30, 48 or 72 centimeters: 13, 25, 51, 76, 122, or 183 10" / 25 cm Blade Pitch 15° 6" / 15 cm 42", 52" or 60" / 107 cm, 132 cm or 152 cm

**Blade Options** 



	SUI	P	ER	J	AN	ET
	FINIS	SH A	AND BLA	ADE		IS
	SKI	U#	SJ-XX-			+Diameter)
ickel	Standard Finish	ies	Brushed Gloss W Matte B Texture	d Nic Vhite Black	ckel	BN WH BK TB
des	Blade Finisł	nes	Barn W Matte B Matte V Walnut	ood Black Vhite	Tone c	BW BK MWH WN
	Fan Diame	ter	52 inch	es /	107 cm 132 cm 152 cm	42 52 60
		ΤE	CHNICA	L SF	PECS	
	Fan Diamet	er			52 or 60 :: 107, 132	or 152
	Blade Mater	ial			lid Wood	01 102
	Overall Dro	эр	12 inche	s/3	0 cm + do	wnrod length
	Fan Weig	ht	17 lbs			
	Downrods Lengt Field cuttab Non-thread	le.			, 20, 30, 4 : 13, 25, 51	18, 72 , 76, 122, 183
	Downrod Diamet	er	1 inch			
	Volta	ge	110 (Cor	ntact	us for 22	0 conversion)
	Motor Ty	ре	DC			
	Environme	nt	Neither	coa	ions for a stal, saltv mpatible	ll finishes vater nor
	Ambien	ce	Silent			
	Safety Certificati	on	ETL / C	ETL		
1	Warran	.,	Limited			
)	NEW JAN 21, 2			_		
	Fan Diameter		2 inch / 07 cm*		2 inch / 32 cm*	60 inch / 152 cm
	RPM (Low/High)		/ 242	-	/ 184	50 / 150
	CFM (Low/High)		5 / 4530	157	1 / 5962	2293 / 6495
	Watts (High)	23.	62	32.	.99	33.32
	CFM/Watt (High)			180		205
	Blade Pitch	15°		15°		15°
				IOTO	METRICS	
	Lamping (Re Remote Di				Integ	rated LED Yes
	Delivered Tem					2776
	Delivered					419
	CR	I				94
	Wat	ts				18
	Hou					0,000
	Light kit longe					22.8 Years
		_	IDARD E		hes / 25 c	
					for up to 3	
	Black 6-speed RF remote control with reverse			Whit	e wireless pra-style, eed, wall	
	NOTE: Only c					
	*Unipack Ship	oing	for 42"a	nd 5	2" in diam	neters only.



The Ar Ruthiane's unique hourglass support arms grasp bullet-shaped motor housings which rotate 360° about its teardrop center. The fan heads can be infinitely positioned in 180-degree arcs for optimum air movement; the greater the angles of the motors to the horizontal support rods (up or down), the faster the axial rotation. A slow, controlled axial rotation is achieved by both fan head position and fan blade speed. Matthews 360° rotational fans circulate heat and air conditioning more efficiently than traditional paddle fans. Constructed of cast aluminum, heavy spun and stamped steel, the Ar Ruthiane carries a limited lifetime warranty.





#### **Special Order Finishes**



		RUTHIA	NE
		AND BLADE OPT	
	SKU#	AR-XXXXXXX-XXX	
	5KU#	(Model+Finish+Bla Black	ade) BK
	Standard Finishes	Bronzette Brushed Nickel	BK BZZT BN
	Special Order Finishes	Brushed Brass Brushed Copper Polished Brass Polished Chrome Polished Copper Polished Chrome I Brushed Nickel Da Gloss White Agua Marinha Ametista Black Nickel Esmeralda Ouro Rubi Safira	
	Fan Blade	Solid Mahogany Wood Blade Metal Blade	WD MTL
	TE	ECHNICAL SPECS	
	Fan Weight	21 lbs	
	Voltage	110 or 220	
í.	Motor Type	AC	
	Rotation	Yes	
	Downrods Lengths Field cuttable. Non-threaded	inches: 5, 10, 20, 3 centimeters: 13, 2	
	Downrod Diameter	.75 inch	
	Overall Drop	-	+ downrod length
	Environment	Damp location w powder or clear o coastal, saltwater compatible.	coaṫ only. Neither
	Ambience	Soothing White N	oise
	Safety Certification	UL / CUL	
	Warranty	Limited Lifetime	
	NEW JAN 21, 2020	DOE MOTOR EFF	ICIENCY DATA
	Fan Head Options	Solid Mahogany Wood	Metal with Guard
7	Fan Diameter	48 inches / 122 cm 16 inches / 41 cm	46 inches / 117 cm
	Fan Blade Diameter Guard Options	No Cage Option	13 inches / 33 cm Decorative Cage or Safety Cage with tight tines
	RPM (Low / High)	723 / 1308	591 / 1075
	CFM (Low / High)	2644 / 4724	1215 / 2371
	Watts (High) CFM/Watt (High)	96.94	103.53 22.90
	Blade Pitch	48.73 19°	22.90 31°
		NDARD EQUIPMEN	
		10 inches / 25 cm	6
	Flat ceili	ng canopy	
		EQUIPMENT	
	29° vaulted ceiling	g mount and canopy	•
a	Standa	rd Finishes	
ned cel np	Gloss Matte White Black		shed kel 65

Spinning Bianca Direcionals in Polished Chrome with wood blades shown

### **Bianca Direcional**



Unique and versatile, the fan head of the Bianca Direcional ceiling fan can be infinitely positioned in a 180-degree arc, forward and reverse, to provide maximum, directional airflow. The Bianca can be hung in small, awkward spaces or in front of HVAC ducts to make more efficient the heating, ventilation or air conditioning of any room. Constructed of cast aluminum, heavy spun and stamped steel, the Bianca Direcional carries a limited lifetime warranty.





#### **Special Order Finishes**

Agua Marinha	Ametista	Black Nickel	Esmeralda	Ouro	Rubi	S
Brushed Brass	Polished Brass	Brushed Copper	Polished Copper	Polished Chrome	Polished Chrome Damp	Bi N

MATTHÉWS

GERBAR

shown in

Brushed Nickel

Brushed Nickel Damp

### **BIANCA** DIRECIONAL FINISH AND BLADE OPTIONS

FINISH	AND BLADE OP	HONS
SKU#	BD-XXXXXX-XX (Model+Finish+B	lade)
Standard Finishes	Black Bronzette Brushed Nickel	BK BZZT BN
Special Order	Brushed Brass Brushed Copper Polished Brass Polished Chrome Polished Copper Polished Chrome Brushed Nickel D Gloss White Agua Marinha Ametista Black Nickel Esmeralda Ouro Rubi Safira	
Fan Blade	Solid Mahogany Wood Blade Metal Blade	WD MTL
т	ECHNICAL SPECS	
Fan Weight	7 lbs	
Voltage	110 or 220	
Motor Type	AC	
Oscillation	No	
Downrods Lengths		
Field cuttable. Non-threaded	inches: 5, 10, 20, centimeters: 13, 2	
Downrod Diameter	.75 inch	
Overall Drop		13 inches / 33 cm + downrod length
	Wood Blades: Damp location wi	16 inches / 41 cm + downrod length ith protective
Environment	powder or clear o coastal, saltwater compatible.	oat only. Neither
Ambience	Soothing White N	loise
Safety Certification	UL / CUL	
Warranty	Limited Lifetime	
NEW JAN 21, 2020	DOE MOTOR EF	FICIENCY DATA
Fan Head Options	Solid Mahogany Wood	Metal with Guard
Fan Diameter	16 inches / 41 cm	13 inches / 33 cm
Fan Blade Diameter	16 inches / 41 cm	13 inches / 33 cm
Guard Options	No Cage Option	Decorative Cage or Safety Cage with tight tines
RPM (Low / High)	926 / 1280	615 / 1149
CFM (Low / High)	1568 / 2274	814 / 1199
Watts (High)	47.46	49.00
CFM/Watt (High)	47.91	24.47
Blade Pitch	19°	31°
STAL	NDARD EQUIPME	NT
	10 inches / 25 cm	
	ng canopy	
(Not compatible with		opy)
Decora-style, 3-spee	d wall control in wh	nite
Standa	rd Finishes	
Class	Durantesta	shad

Gloss White

ronzette

∕latte

Black

Brushed Nickel

67



68

8	2	1		
Ì	H			
Ŷ,	4	X	ľ	Ŋ
Y S		1	ļ	1
2		1		
7				
/				







BRI	SA 200	00
FINISH	AND BLADE OPT	IONS
SKU#	B2K-XXXXXXX-XX (Model+Finish+Bla	
Standard Finishes	Black Bronzette Brushed Nickel	BK BZZT BN
Special Order	Brushed Brass Brushed Copper Polished Brass Polished Chrome Polished Copper Polished Chrome I Brushed Nickel Da Gloss White Agua Marinha Ametista Black Nickel Esmeralda Ouro Rubi Safira	
Fan Blade	Solid Mahogany Wood Blade Metal Blade	WD MTL
TE	ECHNICAL SPECS	
Fan Weight	21 lbs	
Voltage	110 or 220	
Motor Type	AC	
Rotation	Yes	
Downrods Lengths Field cuttable. Non-threaded	inches: 5, 10, 20, 3 centimeters: 13, 2	30, 48, 72 5, 51, 76, 122, 183
Downrod Diameter	.75 inch	
Overall Drop	10 inches / 25 cm	+ downrod length
Environment	Damp location wi powder or clear c coastal, saltwater compatible.	oat only. Neither
Ambience	Soothing White N	oise
Safety Certification	UL/CUL	
Warranty	Limited Lifetime	
NEW JAN 21, 202	0 DOE MOTOR EFF	FICIENCY DATA
Fan Head Options	Solid Mahogany Wood*	Metal with Guard
Fan Diameter	40 inches /102 cm	39 inches/99 cm
Fan Blade Diameter	16 inches/41 cm	13 inches / 33 cm
Guard Options	No Cage Option	Decorative Cage or Safety Cage with tight tines
RPM (Low / High)	866 / 1336	790 / 1205
CFM (Low / High)	1602 / 2376	790 / 1265
Watts (High)	52.44	55.15
CFM/Watt (High)	45.31	22.94
Blade Pitch	19°	31°
STAI	NDARD EQUIPMEN	п
One downrod of	f 10 inches / 25 cm	6
Flat ceili	ng canopy	
Decora-style, 3-spee	• • • •	te
OPTIONAL	EQUIPMENT	
	g mount and canopy	
	k Shipping for Wood	

DDICA 2000

Brushed Nickel Damp



#### **Standard Finishes**



Brushed Nickel



# Bruna Parede

161



The Bruna Parede is reminiscent of the wall fans of the early 20th century. The fan head of the Bruna Parede wall mounted fan can be infinitely positioned vertically and horizontally across 180-degree arcs to provide maximum directional airflow. It can be mounted in small, awkward spaces or in front of HVAC ducts to make more efficient the heating, ventilation or air conditioning of any space. Constructed of cast aluminum, heavy spun and stamped steel, the Bruna Parede carries a limited lifetime warranty.





Ouro Polished Chrome Damp Polished Copper Polished Chrome Brushed Polished Brushed Brass Brass Copper

/IATTHEWS GERBAR

	B	BRUNA	
		AREDE	
	<b>P</b> A	AREDE	
	FINISH /	AND BLADE OPTIONS	
	SKU#	BP-XXXXXX (Model+Finish)	
	Standard Finishes	Black Bronzette Brushed Nickel	BK BZZT BN
	Special Order	Brushed Brass Brushed Copper Polished Brass Polished Chrome Polished Chrome Damp Brushed Chrome Damp Gloss White Agua Marinha Ametista Black Nickel Esmeralda Ouro Rubi Safira	BRBR BRCP PB CR CP CRDAMP BNDAMP WH LTBLUE LTPURPLE BKN GREEN GREEN GOLD RED BLUE
	TE		BEUE
	Fan Weight	8 lbs	
	Blade Material	Metal	
M	Voltage	110 or 220	
	Motor Type	AC	
	Oscillation	No	
	Fan Diameter	13 inches / 33 cm	
11	Fan Height	21 inches / 51 cm	
/	Fan Projection	16 inches / 41 cm	
	Recommended Mounting Height	Approximately 24 inches 61 cm from ceiling	5 /
	Fan Guard	Safety Cage	
	Environment	Damp location with pow coat only. Neither coast nor chlorine compatible	al. saltwater
	Ambience	Soothing White Noise	
	Safety Certification	UL / CUL	
	Warranty	Limited Lifetime	
	NEW JAN 21, 2020	DOE MOTOR EFFICIEN	ICY DATA
	RPM (Low / High)	1021 / 1418	
	CFM (Low / High)	839 / 1181	
	Watts (High)	49.00	
	CFM/Watt (High)	24.01	
	Blade Pitch	31°	
		NDARD EQUIPMENT	
		y cage	0
		wall junction box d wall control in white	



#### **Standard Finishes**





shown in Polished Chrome with metal blades and decorative cage

GERBAR

NCTLY HE

· · · · ·

hown in Black with netal blades in decorative cage

# Duplo-Dinamico

Few designs can match the timeless and sophisticated aesthetic of the Duplo-Dinamico 360° rotational fan. Other manufacturers have tried to reproduce this unique design, though all have proven to be of lesser quality and durability. The fan heads can be infinitely positioned in 180-degree arcs for optimum air movement; the greater the angles of the motors to the horizontal support rods (up or down), the faster the axial rotation. A slow, controlled axial rotation is achieved by both fan head position and fan blade speed. Matthews 360° rotational fans circulate heat and air conditioning more efficiently than traditional paddle fans. Constructed of cast aluminum, heavy spun and stamped steel, the Duplo carries a limited lifetime warranty.







	5	
	X	
J	()	
7	1	
/		

vith wood blades



			_
,	or	183	
			-



	DUPLC	DINA	MICO
	FINISH	AND BLADE OPT	IONS
	SKU#	DD-XXXXXXX-XXX (Model+Finish+Bla	{
	Standard Finishes	Black Bronzette Brushed Nickel	BK BZZT BN
	Special Order	Brushed Brass Brushed Copper Polished Brass Polished Chrome Polished Chrome I Brushed Nickel Da Gloss White Agua Marinha Ametista Black Nickel Esmeralda Ouro Rubi Safira	
	Fan Blade	Solid Mahogany Wood Blade	WD
	Fail blade	Metal Blade	MTL
-	TE	CHNICAL SPECS	
	Fan Weight	21 lbs	
	Voltage	110 or 220	
	Motor Type	AC	
	Rotation	Yes	
	Downrods Lengths <i>Field cuttable.</i>	inches: 5, 10, 20, 3	
	Non-threaded	centimeters: 13, 25	o, 51, 76, 122, 183
	Downrod Diameter	.75 inch	
	Overall Drop	9 inches / 23 cm +	
	Environment	Damp location wi powder or clear c coastal, saltwater compatible.	oat only. Neither
	Ambience	Soothing White N	oise
	Safety Certification	UL / CUL	
	Warranty	Limited Lifetime	
	NEW JAN 21, 2020		ICIENCY DATA
	Fan Head Options	Solid Mahogany Wood*	Metal with Guard
	Fan Diameter	36 inches / 91 cm	39 inches/99 cm
	Fan Blade Diameter	16 inches/41 cm	13 inches / 33 cm
	Guard Options	No Cage Option	Decorative Cage or Safety Cage with tight tines
	RPM (Low / High)	1274 / 1534	598 / 1109
	CFM (Low / High)	2673 / 3210	1240 / 2274
	Watts (High)	74.06	103.35
	CFM/Watt (High)	43.34	22.00
	Blade Pitch	19°	31°
		10 inches / 25 cm	2
		ng canopy d wall control in whi	ta
		EQUIPMENT	
		k Shipping for Wood	

#### **Standard Finishes**



Brushed Nickel



The Italo Ventania is the largest 360° rotational fan in the Matthews Fan Co collection. Its vortex sculpted arms grasp also remarkable, side-mounted fan heads in gentle, equatorial rotation. The fan heads can be infinitely positioned in 180-degree arcs for optimum air movement; the greater the angle of the motor to the horizontal support rods (up or down), the faster the axial rotation. A slow, controlled axial rotation is achieved by both fan head position and fan blade speed. Matthews 360° rotational fans circulate heat and air conditioning more efficiently than traditional paddle fans. Constructed of cast aluminum, heavy spun and stamped steel, the Ar Ruthiane carries a limited lifetime warranty.



Downrods available in inches: 5, 10, 20, 30, 48 or 72 centimeters: 13, 25, 51, 76, 122, or 183 (5.5" diameter ceiling canopy is used with 5" downrod) 10" / 25 cm 4" / 10 cm 62"/ 157 cm wood fan head | 60" / 152 cm metal fan head Increasing Angles of Fan Heads to Support Poles Increases Speed of Axial Rotation Optimum Fan Head Position is 60° **Special Order Finishes** Ouro Polished Chrome Brushed Polished Brushed Polished Brass Brass Copper Copper

shown in

Fan Blade TE Fan Weight Voltage	Ouro Rubi Safira Solid Mahogany Wood Blade Metal Blade	GOLD RED BLUE
TE Fan Weight	Wood Blade Metal Blade	WD
Fan Weight	CUNICAL CDECC	MTL
-	CHNICAL SPECS	
Voltage	24 lbs	
	110 or 220	
Motor Type	AC	
Rotation	Yes	
Downrods Lengths Field cuttable. Non-threaded	inches: 5, 10, 20, 3 centimeters: 13, 2	
Downrod Diameter	.75 inch	
Overall Drop	14 inches / 36 cm	+ downrod lengt
Environment	Damp location wit powder or clear co coastal, saltwater r compatible.	bat only. Neither
Ambience	Soothing White No	oise
Safety Certification	UL / CUL	
Warranty	Limited Lifetime	
NEW JAN 21, 2020		ICIENCY DATA
Fan Head Options	Solid Mahogany Wood	Metal with Gua
Fan Diameter	62 inches / 157 cm	60 inches / 152
Fan Blade Diameter	16 inches/41 cm	13 inches / 33 c
Guard Options	No Cage Option	Decorative Cag or Safety Cage with tight tines
RPM (Low / High)	715 / 1209	685 / 1139
CFM (Low / High)	2644 / 4519	1372 / 2278
Watts (High)	91.63	94.76
CFM/Watt (High)	49.32	24.04
Blade Pitch	19°	31°
STAN	NDARD EQUIPMEN	т
One downrod of 1		







# Jarold Direcional

MATTHÉWS GERBAR

Unique and versatile, the fan head of the Jarold Direcional ceiling fan can be infinitely positioned in a 180-degree arc, forward and reverse, to provide maximum, directional airflow. The Jarold can be hung in small, awkward spaces or in front of HVAC ducts to make more efficient the heating, ventilation or air conditioning of any room. Constructed of cast aluminum, heavy spun and stamped steel, the Jarold Direcional carries a limited lifetime warranty.







		J DIR
		FINISH
14		SKU#
A.	Standard	Finishes
	Spec	cial Orde
	F	- an Blade
in		
vith Iades	Fai	n Weight
y cage		Voltage
		tor Type
	O Downrods	scillation
	Field	cuttable.
ALC: N	/von- Downrod	<i>threaded</i> Diameter
		rall Drop
	Envi	ronment
	A	mbience
1	Safety Cer	tification
1 or 76		Narranty
	NEW JAN	
	Fan Heac	-
		Diameter
	Fan Blade	Diametei
	Guarc	Options
	RPM (Lov	
	CFM (Lov	
top		ts (High) tt (High)
n of .:		ade Pitch
es es		ST/
	One d	ownrod
	(Not compa Decora-sty	
Safira	<u> </u>	
		Stand

JAROLD					
DIRECIONAL					
FINISH /	AND BLADE OP	TIONS			
SKU#	JD-XXXXXXX-XX (Model+Finish+B	lade)			
Standard Finishes	Black Bronzette Brushed Nickel	BK BZZT BN			
Special Order	Brushed Brass Brushed Copper Polished Chrome Polished Chrome Brushed Chrome Brushed Nickel D Gloss White Agua Marinha Ametista Black Nickel Esmeralda Ouro Rubi Safira				
Fan Blade	Solid Mahogany Wood Blade Metal Blade	WD MTL			
TI	ECHNICAL SPECS				
Fan Weight	7 lbs				
Voltage	110 or 220				
Motor Type	AC				
Oscillation	No				
Downrods Lengths Field cuttable. Non-threaded	inches: 5, 10, 20, 30 centimeters: 13, 25, 51, 76				
Downrod Diameter	.75 inch				
Overall Drop	'				
	Wood Blades:         + downrod length           Damp location with protective powder or clear coat only. Neither				
Environment	coastal, saltwater nor chlorine compatible.				
Ambience	Soothing White N	loise			
Safety Certification	UL / CUL				
Warranty	Limited Lifetime				
NEW JAN 21, 2020	DOE MOTOR EF	FICIENCY DATA			
Fan Head Options	Solid Mahogany Wood	Metal with Guard			
Fan Diameter	16 inches / 41 cm	13 inches / 33 cm			
Fan Blade Diameter	16 inches / 41 cm	13 inches / 33 cm			
Guard Options	No Cage Option	Decorative Cage or Safety Cage with tight tines			
RPM (Low / High)	955 / 1318	615 / 1149			
CFM (Low / High)	1701 / 2368	800 / 1162			
Watts (High)	46.77	48.39			
CFM/Watt (High)	50.63	24.01			
Blade Pitch 19° 31° STANDARD EQUIPMENT					
One downrod of 10 inches / 25 cm					
Flat ceiling canopy					
(Not compatible with vaulted ceiling canopy)					
Decora-style, 3-speed	d wall control in wh	nite			

#### Standard Finishes







shown in Polished Chrome with metal blades

GERBAR



The Michelle Parede is reminiscent of wall fans of the early 20th century. The fan head of the Michelle Parede wall mounted fan can be infinitely positioned vertically and horizontally across 180-degree arcs to provide maximum directional airflow. It can be mounted in small, awkward spaces or in front of HVAC ducts to make more efficient the heating, ventilation or air conditioning of any space. Constructed of cast aluminum, heavy spun and stamped steel, the Michelle Parede carries a limited lifetime warranty.





### MICHELLE PAREDE

FINISH .	AND BLADE OPTION	S
SKU#	MP-XXXXXX (Model+Finish)	
Standard Finishes	Black Bronzette Brushed Nickel	BK BZZT BN
Special Order	Brushed Brass Brushed Copper Polished Brass Polished Chrome Polished Chrome Damp Brushed Nickel Damp Gloss White Agua Marinha Ametista Black Nickel Esmeralda Ouro Rubi Safira	BRBR BRCP PB CR CP O CRDAMP BNDAMP WH LTBLUE LTPURPLE BKN GREEN GOLD RED BLUE
Т	ECHNICAL SPECS	
Fan Weight	8 lbs	
Blade Material	Metal	
Voltage	110 or 220	
Motor Type	AC	
Oscillation	No	
Fan Diameter	13 inches / 33 cm	
Fan Height	20 inches / 51 cm	
Fan Projection	16 inches / 41 cm	
Recommended Mounting Height	Approximately 24 inch 61 cm from ceiling	es /
Fan Guard	Safety Cage	
Environment	Damp location with powder or clear coat only. Neither coastal, saltwater nor chlorine compatible.	
Ambience	Soothing White Noise	
Safety Certification	UL / CUL	
Warranty	Limited Lifetime	
NEW JAN 21, 2020	DOE MOTOR EFFICIE	NCY DATA
RPM (Low / High)	1020 / 1418	
CFM (Low / High)	838 / 1181	
Watts (High)	49.00	
CFM/Watt (High)	24.01	
Blade Pitch	31°	
STAN	NDARD EQUIPMENT	
Safet	y cage	0
Side-mounted wall junction box		
Decora-style, 3-spee	d wall control in white	

Polished Chrome Damp Brushed Nickel Damp Gloss White

#### **Standard Finishes**



Brushed Nickel



shown in Bronzette with metal blades



# Vent-Bettina



The Vent-Bettina 360° rotational fan is thoughtfully designed with its arms gently upward curving. The fan offers fluid lines and quiet axial rotation with motor heads which can be infinitely positioned in 180-degree arcs for optimum air movement; the greater the angles of the motors to the horizontal support rods (up or down), the faster the axial rotation. A slow, controlled axial rotation is achieved by both fan head position and fan blade speed. Matthews 360° rotational fans circulate heat and air conditioning more efficiently than traditional paddle fans. Constructed of cast aluminum, heavy spun and stamped steel, the Vent-Bettina carries a limited lifetime warranty.





VEN	Г-ВЕТТ	INA		
FINISH /	AND BLADE OPT	IONS		
SKU#	VB-XXXXXX-XXX (Model+Finish+Bla			
Standard Finishes	Black Bronzette Brushed Nickel	BK BZZT BN		
Special Order	Brushed Brass Brushed Copper Polished Brass Polished Chrome Polished Chrome I Brushed Chrome I Brushed Nickel Da Gloss White Agua Marinha Ametista Black Nickel Esmeralda Ouro Rubi Safira			
Fan Blade	Solid Mahogany Wood Blade Metal Blade	WD MTL		
TE	CHNICAL SPECS			
Fan Weight	19 lbs			
Voltage	110 or 220			
Motor Type	AC			
Rotation	Yes			
Downrods Lengths Field cuttable. Non-threaded	inches: 10, 20, 30, 48, 72 centimeters: 25, 51, 76, 122, 183			
Downrod Diameter	.75 inch			
Overall Drop	7 inches / 18 cm + downrod length			
Environment	Damp location with protective powder or clear coat only. Neither coastal, saltwater nor chlorine compatible.			
Ambience	Soothing White Noise			
Safety Certification	UL / CUL			
Warranty	Limited Lifetime			
NEW JAN 21, 2020	DOE MOTOR EFF	ICIENCY DATA		
Fan Head Options	Solid Mahogany Wood	Metal with Guard		
Fan Diameter	44 inches /112 cm	42 inches /107 cm		
Fan Blade Diameter	16 inches/41 cm	13 inches / 33 cm		
Guard Options	No Cage Option	Decorative Cage or Safety Cage with tight tines		
RPM (Low / High)	796 / 1252	699 / 1101		
CFM (Low / High)	2070 / 329	1346 / 2077		
Watts (High)	87.32	89.63		
CFM/Watt (High)	37.71	23.17		
Blade Pitch	19°	31°		
STANDARD EQUIPMENT				
One downrod of 10 inches / 25 cm				
Flat ceiling canopy				
Decora-style, 3-speed wall control in white OPTIONAL EQUIPMENT				
29° vaulted ceiling mount and canopy				



**Standard Finishes** 

